



MOJAVE DESERT AIR QUALITY MANAGEMENT DISTRICT

14306 Park Avenue Victorville, CA 92392-2310
760.245.1661 -- 800.635.4617 -- FAX 760.245.2022

RENEWAL

B013064

Renewal type Permit has no description information.

EXPIRES LAST DAY OF: JUNE 2025

OWNER OF OPERATOR (Co.#2887)

Double D Mining, LLC
P.O. Box 7060
Visalia, CA 93290

EQUIPMENT LOCATION (Fac.#3707)

Double D Mining, LLC
1 Arlington Mine Road
Blythe, CA 92225

Description:

TRUCK LOAD OUT consisting of:

EQUIPMENT

Capacity	Equipment Description
0	feed hopper
20	conveyor - verify HP

CONDITIONS:

1. This equipment shall be installed, operated and maintained in strict accordance with those recommendations of the manufacturer/supplier and/or sound engineering principles which produce the minimum emissions of contaminants. Unless otherwise noted, this equipment shall also be operated in accordance with all data and specifications submitted with the application for this permit. [District Rules 204 and 1302]

2. This equipment shall be powered by an internal combustion diesel engine with a valid District permit. [District Rules 1302 and 1320]

Fee Schedule: 1 (a) Rating: 20bhp SIC: 1499 SCC: 30501503 Location/UTM(Km): 700E/3743N

This permit does not authorize the emission of air contaminants in excess of those allowed by law, including Division 26 of the Health and Safety Code of the State of California and the Rules and Regulations of the District. This permit cannot be construed as permission to violate existing laws, ordinances, statutes or regulations of this or other governmental agencies. This permit must be renewed by the expiration date above. If billing for renewal fee required by Rule 301(c) is not received by expiration date above, please contact the District.

Double D Mining, LLC
P.O. Box 7060
Visalia, CA 93290

By: **COPY**
Brad Poiriez
Air Pollution Control Officer

3.Roadways, work areas and stockpiles shall be kept wetted to control fugitive dust. Equipment to properly wet the material being processed shall be maintained in operable condition on-site and used as necessary to assure compliance. This does not include the haul roads outside of the fenced facility.

[District Regulation IV]

4.This equipment shall not discharge into the atmosphere an exhaust stream that exhibits an opacity during any one hour (ten 6-minute averages) greater than seven (7) percent opacity from all transfer points and fugitive emission points.

[40 CFR 60.672]

5.A facility log shall be maintained on-site and made available to District personnel upon request. This log shall contain, at a minimum:

(a) Dates this equipment is moved from one location to another, and permit unit associated with or location of use if used independently, applies to radial stackers only;

(b) Records of 40 CFR 60, Subpart OOO initial compliance testing required by condition 8; and,

(c) 12 month rolling average PM10 emissions in ton/year as required by condition 11; and,

(d) Hours operated per day.

[District Rules 204 and 1302]

6.The owner/operator shall conduct an initial compliance test per NSPS Subpart OOO requirements, including opacity (USEPA Method 9 or equivalent) testing as applicable for each fugitive emission point (transfer point or other) associated with this equipment. The initial compliance test must be conducted no later than September 10, 2018. Compliance test shall be carried out in accordance with the test methods defined in 40 CFR 60 Subpart OOO Section 60.675 and the District Compliance Test Procedural Manual.

[40 CFR 60.672]

The owner/operator must submit a compliance/certification test protocol at least thirty (30) days prior to the compliance/certification test date. The owner/operator must conduct all required compliance/certification tests in accordance with a District-approved test protocol. The owner/operator must notify the District a minimum of ten (10) days prior to the compliance/certification test date so that an observer may be present. The final compliance/certification test results must be submitted to the District within forty-five (45) days of completion of the test. All compliance/certification test notifications, protocols, and results may be submitted electronically to reporting@mdaqmd.ca.gov

7.In the event of any equipment malfunction or breakdown as defined in District Rule 430, the event must be reported to the District within one hour.

[District Rule 430]

8.Operation of this equipment is limited to:

(a) 2 hr/day; and,

(b) 50 ton/hr.

[Rule 1303 BACT, Offsets]

9.The facility shall not emit more than 14.9 tons of PM10.Compliance with this limit shall be demonstrated by a 12 month rolling average.

[District Rule 1303(B) Offsets]

10.Existing equipment cannot be replaced and/or new equipment cannot be added without submitting an application to the District and receiving a new Permit from the District.

[District Regulation XIII - NSR]

11.This equipment shall be operated in compliance with all applicable requirements of 40 CFR 60, Subpart OOO - Standards of Performance for Nonmetallic Mineral Processing Plants. In the event of conflict between Permit conditions and the requirements of 40 CFR 60, Subpart OOO, the more stringent requirements shall govern.