



MOJAVE DESERT AIR QUALITY MANAGEMENT DISTRICT

14306 Park Avenue Victorville, CA 92392-2310
760.245.1661 -- 800.635.4617 -- FAX 760.245.2022

INACTIVE

T003093

Inactive type Permit has no description information.

EXPIRES LAST DAY OF: NOVEMBER 2015

OWNER OF OPERATOR (Co.#87)

Commanding Officer, MCLB Barstow, CA
Box 110570 Bldg 196 Attn: Air Program Manager
Barstow, CA 92311-5050

EQUIPMENT LOCATION (Fac.#587)

USMC MCLB - Yermo Annex
USMC Logistics Base
Barstow, CA 923115013

Description:

DIP TANK consisting of: Tank #14, Soluble Oil. Surface Area of Solvent: 18 sq. ft. (3' x 6') Volume of Solvent: 470 gallons (3' x 6' x 3.5')
Agent: Soluble Oil, Boiling Point 700 °F, Specific Gravity 0.93, Autoignition Temp. 340 °F, Flash Point 340 °F. Operating Temperature: 200 °F Cover for Top

EQUIPMENT

Capacity	Equipment Description
0	Surface Area of Solvent: 18 sq. ft. (3'x6')
0	Volume of Solvent: 470 gallons (3'x6'x3.5')
0	Agent: Soluble Oil, Boiling Point 700 degrees F, Specific Gravity 0.93, Autoignition Temp. 340 degrees F, Flash Point 340 degrees F.
0	Operating Temperature: 200 degrees F
0	Cover for Top
0	Electric Heated Pad

CONDITIONS:

1. The tank shall be equipped with a tight fitting cover that shall be closed at all times when the tank is not in use.
2. The tank must have a Freeboard Height of at least five (5) inches while the item(s) are submerged. The Freeboard Height is the distance from the top of the liquid to the top of the tank.

Fee Schedule: 5 (a)

Rating: 500 gallons

SIC: 9711

SCC: 99999999

Location/UTM(Km):
512E/3861N

This permit does not authorize the emission of air contaminants in excess of those allowed by law, including Division 26 of the Health and Safety Code of the State of California and the Rules and Regulations of the District. This permit cannot be construed as permission to violate existing laws, ordinances, statutes or regulations of this or other governmental agencies. This permit must be renewed by the expiration date above. If billing for renewal fee required by Rule 301(c) is not received by expiration date above, please contact the District.

Commanding Officer, MCLB Barstow, CA
Box 110570 Attn: Air Program Manager
Barstow, CA 92311-5050

By: **COPY**
Brad Poiriez
Air Pollution Control Officer

3. Parts shall be added or removed from the tank in a manner so as to prevent splashing.
4. Do not remove parts from the dip tank until the parts are visually dry and not dripping/leaking solvent. [1104(C)(2)(vi)(e)]
5. The hoist speed must be slow enough to prevent solvent vapors from being pushed and/or pulled out of the tank. The speed of the existing hoist must not exceed 30 feet per minute and any new or replacement hoist must not exceed 11.2 feet per minute.
6. An operator's log must be maintained which contains, as a minimum, the type of solvent in each tank, date and amount of solvent added, and a daily self-inspection checklist. The log shall be maintained on-site for at least five (5) years and provided to District, State or Federal personnel on request.
7. The dip tank shall only be operated and maintained in strict accord with manufacturer's/supplier's recommendations and/or sound engineering principles.