

MOJAVE DESERT AIR QUALITY MANAGEMENT DISTRICT

14306 Park AvenueVictorville, CA92392-2310 760.245.1661 -- 800.635.4617 -- FAX760.245.2022

RENEWAL

B008529

Renewal type Permit has no description information.

EXPIRES LAST DAY OF:SEPTEMBER 2025

OWNER OF OPERATOR (Co. #503)

EQUIPMENT LOCATION (Fac.#2375)

Robertson's Ready Mix P.O.Box 3600 Corona,CA92878 Robertson's Ready Mix - Ft Irwin Rd 58825 Ft. Irwin Road Barstow,CA92310

Description:

READY MIX CONCRETE consisting of:

EQUIPMENT

Capacity	Equipment Description
15	C-1 Belt Conveyor
15	C-2 Belt Conveyor
15	C-3 Belt Conveyor
15	C-4 Belt Conveyor
15	C-5 Charge Conveyor
30	A-2 Flyash auger
20	Compressor
7.5	Compressor
10	Water Pump
20	Water Pump
5	Water Pump

CONDITIONS:

1. Operation of the equipment described above shall be conducted as described in the data and specifications submitted with the application under which this permit is issued unless specifically exempted hereunder.

Fee Schedule:1 (b)

Rating:167.5bhp

SIC:1422

SCC:30501109

Location/UTM(Km):518E/3884N

This permit does not authorize the emission of air contaminants in excess of those allowed by law, including Division 26 of the Health and Safety Code of the State of California and the Rules and Regulations of the District. This permit cannot be construed as permission to violate existing laws, ordinances, statutes or regulations of this or other governmental agencies. This permit must be renewed by the expiration date above. If billing for renewal fee required by Rule 301(c) is not received by expiration date above, please contact the District.

Robertson's Ready Mix P.O. Box 3600 Corona, CA92878-3600

By: COPY

Brad Poiriez

Air Pollution Control Officer

- 2. This concrete batch plant shall not be operated unless the Weigh Hopper discharge, and Truck Loadout shroud are vented to a properly functioning air pollution control device under valid District permit C008539. Additionally, the Cement and flyash silo's must have properly operating and maintained vent filters.
- 3. This concrete batch plant shall only be operated/maintained in strict accord with manufacturer's supplier's recommendations and/or sound engineering principles.
- 4.Roadways, work areas, stock piles, and materials being processed shall be kept wetted to control fugitive dust. Equipment to properly wet the material being processed shall be maintained in operable condition on-site and used as necessary to assure compliance.
- 5. Water sprays shall be used at conveyor points of charge and discharge to control fugitive emissions.
- 6.Daily production logs shall be maintained at either the facility or corporate office for at two (2) years and available to District, State, or Federal personnel upon request. This log shall contain, as a minimum, the cubic yard of concrete mix produced per day and the total number of hours operated.
- 7.The owner/operator shall comply with all applicable Rules and Regulations of the District. Applicable rules include, but are not necessarily limited to Rules 401, 402, 403, 404, 405, and 430.
- 8. This facility shall emit less than the following limits:
- a. 8 tons per year of any single HAP or 20 tons per year of any combination of HAPs
- b. 12 tons of PM10
- c. 20 tons of NOx on a rolling twelve month summary basis

Compliance with this limit shall be verified with monthly facility emission summaries and an annual emissions inventory. Monthly emissions summaries shall be calculated using a District-approved method, with at least the last two years of monthly emissions summaries maintained for a minimum of two years and provided to District, State or Federal personnel upon request. A facility wide Comprehensive Emission Inventory (CEI) for all emitted criteria and toxic air pollutants must be submitted to the District, in a format approved by the District, upon District request.

[District Rule 107(b); H&S Code 39607 & 44341-44342; and 40 CFR 51, Subpart A]

Page 2 of 2 Permit:B008529 Issue Date:09/04/2024