



## MOJAVE DESERT AIR QUALITY MANAGEMENT DISTRICT

14306 Park Avenue Victorville, CA 92392-2310  
760.245.1661 -- 800.635.4617 -- FAX 760.245.2022

### AUTHORITY TO CONSTRUCT

C012194

If construction is not completed by the expiration date of this permit, it may be renewed for one additional year upon payment of applicable fees. Any additional extension will require the written approval of the Air Pollution Control Officer. This Authority to Construct may serve as a temporary Permit to Operate provided the APCO is given prior notice of intent to operate and the Permit to Operate is not specifically denied.

#### EXPIRES LAST DAY OF: JUNE 2025

#### OWNER OF OPERATOR (Co.#1)

CEMEX Construction Materials Pacific LLC  
16888 North E Street  
Victorville, CA 92392

#### EQUIPMENT LOCATION (Fac.#5)

CEMEX - Black Mountain Quarry Plant  
25220 Black Mountain Quarry Road  
Apple Valley, CA 92307

#### Description:

LISBH1 SILO - BAGHOUSE consisting of: Kiln Q2 Lime Silo air jet type Baghouse, manufactured by WAM, contains 7 polyester woven cartridges, 67 X 429 mm each, total filter area is 24.5 sq meters, flow rate of 1600 Nm<sup>3</sup>/hr, flow velocity of 0.018 m/s, inlet dust concentration of 15750 mg/Nm<sup>3</sup>, outlet dust concentration of 2.65 mg/Nm<sup>3</sup>, duct density is 1.13 Kg/dm<sup>3</sup>. Serves Limestone Storage Silo permitted under T012193 Facility has specified that the normal operating range for pressure differential is between 1 and 5 inches water column.

#### CONDITIONS:

1. This baghouse shall be operated in compliance with applicable requirements of 40 CFR 60 Subpart F - Standards of Performance for Portland Cement Plants and 40 CFR 63 Subpart LLL - National Emission Standard for Hazardous Air Pollutants From the Portland Cement Manufacturing Industry. [Rule 204]
2. This baghouse shall not discharge into the atmosphere an exhaust stream that exhibits greater than ten percent opacity [40 CFR Part 63 Subpart LLL Section 63.1345].
3. This baghouse shall not discharge PM10 in excess of 0.005 grains/dscf (BACT) at the operating conditions given in the above description. [Rule 1302]
4. The o/o shall conduct a minimum program of inspection and maintenance on this equipment. The o/o shall maintain current and on-site for five (5) years a log of the following information, which shall be provided to District, State or Federal personnel upon request:

Fee Schedule: 7 (h)      Rating: 1 device      SIC: 3241      SCC: 30500606      Location/UTM(Km): 476E/3826N

This permit does not authorize the emission of air contaminants in excess of those allowed by law, including Division 26 of the Health and Safety Code of the State of California and the Rules and Regulations of the District. This permit cannot be construed as permission to violate existing laws, ordinances, statutes or regulations of this or other governmental agencies. This permit must be renewed by the expiration date above. If billing for renewal fee required by Rule 301(c) is not received by expiration date above, please contact the District.

CEMEX Construction Materials Pacific  
LLC  
16888 North E Street  
Victorville, CA 92392

By: **COPY**  
**Brad Poiriez**  
Air Pollution Control Officer

- a. Monthly reading of baghouse pressure drop, date and value;
- b. Quarterly felt cartridge inspection date and results;
- c. Date of cartridge replacements; and
- d. Date and nature of any system repairs [Rule 1302]

5. This equipment shall be installed, operated and maintained in strict accordance with those recommendations of the manufacturer which produce the minimum emissions of contaminants. Unless otherwise noted, this equipment shall also be operated in accordance with all data and specifications submitted with the application for this permit. [Rule 204]

6. The owner/operator shall maintain a record of repairs and maintenance on this equipment and submit it to the District, State, or Federal personal upon request. The record shall be retained for a minimum period of five (5) years. [Rule 204]

7. This air pollution control device shall be fitted with an operating air lock system on each material discharge port and shall be provided with a differential pressure measuring device. The nominal design operational/differential pressure range shall be maintained in accordance with manufacturer's recommendations and/or good engineering practices. [Rule 1302]

8. This air pollution control device shall discharge no more than 0.073 pounds per hour and no more than 0.32 tpy of PM10 at a maximum concentration of 0.005 grains/dscf 0.0044gr/dscf (Manufacturers specification) at the operating conditions given in the above description. [Rule 1303 - NSR Requirements]

9. The owner/operator shall conduct initial opacity observations per Method 9 within 180 days of installation and use manufacturer's emissions data instead of source test results for emissions inventory purposes and to demonstrate compliance with condition 8 above. [Rule 204]

10. This equipment shall not be operated until the road paving project at the Quarry Plant is complete as the emissions from this equipment has been offset by simultaneous emission reductions (SERS) from the road paving project. Road center line is defined as: from lat/long of 34.622956/-117.101988 to a lat/long of 34.619300/-117.103491; this project is 1774 feet long by 39 feet wide; SER's are calculated to be 0.64 tpy of PM-10. This road shall be maintained in good order, free from pot holes and excessive dirt. [Rule 204; Rule 1303]

11. This Baghouse is subject to District Rules and Regulations and the Cement NESHAP 40 CFR 63 Subpart LLL. In the event of conflict the more stringent requirements shall govern. [Rule 204]