



MOJAVE DESERT AIR QUALITY MANAGEMENT DISTRICT

14306 Park Avenue Victorville, CA 92392-2310
760.245.1661 -- 800.635.4617 -- FAX 760.245.2022

INACTIVE

S013628

Inactive type Permit has no description information.

EXPIRES LAST DAY OF: AUGUST 2024

OWNER OF OPERATOR (Co.#1932)

Kustom Bumpers Inc.
11433 Santa Fe Avenue East
Hesperia, CA 92345

EQUIPMENT LOCATION (Fac.#3206)

Kustom Bumpers, Inc.
11433 Santa Fe Avenue East
Hesperia, CA 92345

Description:

SPRAY BOOTH, OPEN FACE consisting of: A custom built open faced spray booth measuring approximately 5 feet wide by 5 feet long by 4 feet high. Exhaust is vented through four 20 inch by 20 inch by 2 inch filters to atmosphere via a 5 bhp fan measuring 12.5 inches in diameter with an estimated flow rate of 5,000 ACFM.

CONDITIONS:

1. This equipment shall be installed, operated and maintained in strict accordance with those recommendations of the manufacturer/supplier and/or sound engineering principles which produce the minimum emissions of contaminants. Unless otherwise noted, this equipment shall also be operated in accordance with all data and specifications submitted with the application for this permit. [District Rules 204 and 1303]
2. Only High Volume Low Pressure (HVLP) spray guns or other spray guns or methods with an equivalent transfer efficiency can be used. The District must be notified of in writing and formally approve of any transfer method other than HVLP spray guns. [District Rule 1116]
3. All coatings, diluents, thinners, solvents, application methods, and record keeping, shall comply with District Rules 442, 1115, 1116, and 1320 in their entirety. [District Rules 442 1115, 1116, 1302]
4. Discharge filters shall be installed and maintained in a tightly mounted and dimensionally stable condition, free from excessive deposits or interference with airflow passages. Differential pressure across the outlet filters shall be kept within the normal operating

Fee Schedule: 7 (h)

Rating: 1 device

SIC: 7532

SCC: 40201619

Location/UTM(Km):
473E/3808N

This permit does not authorize the emission of air contaminants in excess of those allowed by law, including Division 26 of the Health and Safety Code of the State of California and the Rules and Regulations of the District. This permit cannot be construed as permission to violate existing laws, ordinances, statutes or regulations of this or other governmental agencies. This permit must be renewed by the expiration date above. If billing for renewal fee required by Rule 301(c) is not received by expiration date above, please contact the District.

Kustom Bumpers Inc.
11433 Santa Fe Avenue East
Hesperia, CA 92345

By: **COPY**
Eldon Heaston
Air Pollution Control Officer

range of 0.05 to 2.5 inches water column. A differential pressure gauge shall be properly installed and maintained to measure this pressure differential.

[District Rule 1302]

5. All VOC containing materials, whether in its form for intended use or as a waste or used product, shall be stored in nonabsorbent, non-leaking containers which shall be kept closed at all times, except when filling or emptying, and disposed of in a manner to prevent evaporation of VOCs into the atmosphere at the Facility.

[District Rule 442]

6. The total combined VOC emissions from this facility shall be less than 25 lbs/day.

[District Rules 1302, 1320, and 1520]

7. A daily log shall be maintained of the Volatile Organic Compounds (VOCs) used and/or emitted from this facility. The log shall contain at least the following:

- a. Equipment by permit number, or name of operation for unpermitted equipment, that uses materials that contain VOCs;
- b. Type and quantity of coating, diluent, thinner, or solvent material being applied, and its VOC content in pounds per gallon (or grams per liter);
- c. Manufacturer of material, manufacturer's product name, and/or code number;
- d. Quantity of acetone usage in gallons (or liters) per day;
- e. Copies of the Environmental Data Sheet and/or Material Safety Data Sheet (MSDS) for each coating, diluent, thinner, and solvent used; and
- f. Differential pressure across outlet filters.

This log shall be kept current and on-site for a minimum of five years, and provided to District personnel on request.

[District Rules 1115, 1116, 1302]

8. The owner/operator (o/o) shall not use any motor vehicle or mobile equipment coating that contains hexavalent chromium or cadmium (Section 17 CCR 93112 - Airborne Toxic Control Measure for Emissions of hexavalent Chromium and Cadmium from Motor Vehicle and Mobile Equipment Coatings). Compliance with this condition shall be verified by retention of MSDS sheets (or equivalent documentation of chemical content) for all coatings used at the facility for three (3) years, and provide copies of these documents to District, State, or federal personnel upon request.

[17 CCR 93112]

9. Pursuant to 40 CFR 63 subpart HHHHHH, this facility shall not conduct any paint stripping operations on any substrate that use methylene chloride (MeCl)-containing paint stripping formulations. Contact the District for additional controls and conditions if this facility will use any MeCl.

[40 CFR 63 subpart HHHHHH, District Rules 1302 and 1320]

10. Pursuant to 40 CFR 63 subpart HHHHHH, this facility shall not spray apply coatings to metal and plastic surfaces that contain compounds of chromium (Cr), lead (Pb), manganese (Mn), nickel (Ni), or cadmium (Cd).

[40 CFR 63 subpart HHHHHH, District Rule 1302]

11. A facility wide Comprehensive Emission Inventory (CEI) for all emitted criteria and toxic air pollutants must be submitted to the District, in a format approved by the District, upon District request.

[District Rule 107(b), H&S Code 39607 & 44341-44342, and 40 CFR 51, Subpart A]