



MOJAVE DESERT AIR QUALITY MANAGEMENT DISTRICT

14306 Park Avenue Victorville, CA 92392-2310
760.245.1661 -- 800.635.4617 -- FAX 760.245.2022

INACTIVE

B000751

Inactive type Permit has no description information.

EXPIRES LAST DAY OF: OCTOBER 2025

OWNER OF OPERATOR (Co.#90)

Omya (California) Inc
7299 Crystal Creek Road
Lucerne Valley, CA 92356

EQUIPMENT LOCATION (Fac.#461)

Omya - Main Plant
7299 Crystal Creek Road
Lucerne Valley, CA 92356

Description:

CRUSHING AND SCREENING CIRCUIT (SENTINEL) consisting of:

EQUIPMENT

Capacity	Equipment Description
0	31-110 Feed Hopper
75	31-120 Vibrating Feeder, AC Motor
40	31-130 Primary Screen
200	31-140 Jaw Crusher
25	31-150 Conveyor-Crusher discharge
15	31-220 Conveyor-Reject
20	31-160 Conveyor-Picking Feed
25	31-180 Conveyor-Picking
20	31-190 Conveyor-Radial Stacker
5	31-191 Conveyor-Travel Motor

CONDITIONS:

Fee Schedule: 1 (c) Rating: 425bhp SIC: 1422 SCC: 30504030 Location/UTM(Km): 505E/3805N

This permit does not authorize the emission of air contaminants in excess of those allowed by law, including Division 26 of the Health and Safety Code of the State of California and the Rules and Regulations of the District. This permit cannot be construed as permission to violate existing laws, ordinances, statutes or regulations of this or other governmental agencies. This permit must be renewed by the expiration date above. If billing for renewal fee required by Rule 301(c) is not received by expiration date above, please contact the District.

Omya (California) Inc
7225 Crystal Creek Rd
Lucerne Valley, CA 92356

By: **COPY**
Brad Poiriez
Air Pollution Control Officer

- 1.This equipment shall be installed, operated and maintained in strict accordance with those recommendations of the manufacturer/supplier and/or sound engineering principles which produce the minimum emissions of contaminants. Unless otherwise noted, this equipment shall also be operated in accordance with all data and specifications submitted with the application for this permit.
[District Rules 204 and 1302]
- 2.The owner or operator must perform weekly inspections to verify that water is properly flowing through all discharge spray nozzles in the wet suppression system described in District permit C003293. The owner/operator must initiate corrective action within 24 hours and complete corrective action as expediently as practical if they find that water is not flowing properly during such inspections. The owner/operator must record each inspection of the water spray nozzles, including the date of each inspection and any corrective actions taken, in the logbook.
[40 CFR 60.674 (b)]
- 3.The owner/operator will periodically monitor opacity from fugitive emission points according to the following methodology:
 - a. The owner or operator must initially conduct a weekly EPA Method 9 visible emissions evaluation of each affected source. The test must be conducted while the affected source is in operation.
 - b. If no visible emissions are observed in four consecutive weekly tests for any affected source, the owner or operator may decrease the frequency of testing from weekly to monthly for that affected source. If visible emissions are observed during any monthly test, the owner or operator must resume testing of that affected source on a weekly basis and maintain that schedule until no visible emissions are observed in four consecutive weekly tests.
 - c. If no visible emissions are observed during the monthly test for any affected source for six months, the owner or operator may decrease the frequency of testing from monthly to semi-annually for that affected source. If visible emissions are observed during any semi-annual test, the owner or operator must resume testing of that affected source on a monthly basis and maintain that schedule until no visible emissions are observed in six consecutive monthly tests.
[District Rules 1302 and 1303]
- 4.This equipment shall be limited to crushing no more than 600 tons of material per hour, nor more than 10,000 tons of material per day. Furthermore, the total combined throughput of this crusher and that of the crusher described in District permit B012438 shall not exceed 1,500,000 tons of material per year, defined as any consecutive rolling twelve month period.
[District Rule 204]
- 5.Materials processed by this equipment shall contain sufficient moisture to control fugitive dust. For this limestone material, sufficient moisture means 1.5% or greater. The moisture content of the aggregate material shall be analyzed quarterly and as requested by the District according to material moisture test ASTM C566-13 or a District approved equivalent method, except that the sample weight may be reduced if necessary to match the maximum capacity of the testing equipment. Sample locations shall be representative of material feed throughout this crushing / screening plant.
[District Regulations IV and XIII]
- 6.Roadways, work areas and stockpiles shall be kept wetted to control fugitive dust. Equipment to properly wet the material being processed shall be maintained in operable condition on-site and used as necessary to assure compliance. This does not include the haul roads outside of the fenced facility.
[District Regulation IV]
- 7.If the dust suppression system described in District permit C003293 does not prevent Visible Fugitive Dust as defined in District Rule 403.2, then all exterior conveyor belts must be enclosed sufficiently to cover the top and sides of the bulk material being transferred.
[District Rule 403.2(C)(6)(b)]
- 8.This equipment shall not discharge into the atmosphere an exhaust stream that exhibits an opacity during any one hour (ten 6-minute averages) greater than the following;
 - a. Ten (10) percent opacity from all transfer points, screens and fugitive emission points; and
 - b. Fifteen (15) percent opacity from all crushers.
[40 CFR 60.672]
- 9.A facility log shall be maintained on-site for at least two (2) years and made available to District personnel upon request. This log shall contain, at a minimum:
 - a. Tons of product produced per month,

- b. Tons of product produced per consecutive rolling twelve month period,
 - c. Results of the quarterly moisture content tests required by Condition 5,
 - d. Opacity reading results from fugitive emission points required by Condition 3, and
 - e. Records of all inspections, repairs, and maintenance actions performed on the water spray system required by condition 2.
- [District Rules 204 and 1302]

10.This equipment shall be operated in compliance with all applicable requirements of 40 CFR 60 Subpart OOO: Standards of Performance for Nonmetallic Mineral Processing Plants. In the event of conflict between Permit conditions and the requirements of 40 CFR 60 Subpart OOO, the more stringent requirements shall govern.

[District Rule 204]

11.The facility shall not emit more than 12 tons of PM10 nor more than 20 tons of NOx per year to remain under the Synthetic Minor - 80% (SM-80) threshold.

[District Rule 204]

12.This equipment is not to be used to process Hazardous Air Pollutant (HAP) containing materials.

[District Rule 1320]

13.In the event of any equipment malfunction or breakdown as defined in District Rule 430, the event must be reported to the District within one hour.

[District Rule 430]

14.A facility wide Comprehensive Emission Inventory (CEI) for all emitted criteria and toxic air pollutants must be submitted to the District, in a format approved by the District, upon District request.

[District Rule 107(b), H&S Code 39607 & 44341-44342, and 40 CFR 51, Subpart A]