



MOJAVE DESERT AIR QUALITY MANAGEMENT DISTRICT

14306 Park Avenue Victorville, CA 92392-2310
760.245.1661 -- 800.635.4617 -- FAX 760.245.2022

INACTIVE

B009333

Inactive type Permit has no description information.

EXPIRES LAST DAY OF: JULY 2006

OWNER OF OPERATOR (Co.#1575)

Kiewit Pacific
39000 Harvard Rd
Newberry Springs, CA 92365

EQUIPMENT LOCATION (Fac.#2665)

Kiewit Pacific - Fort Cady Road
29802 Fort Cady Road
Newberry Springs, CA 92365

Description:

PORTABLE JAW CRUSHER, SELF-PROPELLED consisting of: a Kolberg-Pacific Pioneer FT 2650 track mounted Jaw Plant, Serial Number 405173 powered by

One Caterpillar, Diesel fired internal combustion engine Model No. C-9 DITA and Serial No. CLJ07455, Direct Injected, Turbo Charged, After Cooled, producing 275 bhp with 6 cylinders at 2200 rpm while consuming a maximum of 15.0 gal/hr. This equipment powers a Crusher Model No. and Serial No. , rated at .

EMISSIONS RATES

Emission Type	Est. Max Load	Unit
CO	1.0	gm/bhp-hr
NOx	3.5	gm/bhp-hr
PM10	0.13	gm/bhp-hr
VOC	1.0	gm/bhp-hr

CONDITIONS:

1. Operation of this equipment shall be conducted in accordance with all data and specifications submitted with the application under which this permit is issued unless otherwise noted below.

Fee Schedule: 1 (c)

Rating: 275 bhp

SIC: 3273

SCC: 20200102

Location/UTM(Km):
529E/3855N

This permit does not authorize the emission of air contaminants in excess of those allowed by law, including Division 26 of the Health and Safety Code of the State of California and the Rules and Regulations of the District. This permit cannot be construed as permission to violate existing laws, ordinances, statutes or regulations of this or other governmental agencies. This permit must be renewed by the expiration date above. If billing for renewal fee required by Rule 301(c) is not received by expiration date above, please contact the District.

Kiewit Pacific
P.O. Box 339
Newberry Springs, CA 92365

By: **COPY**
Eldon Heaston
Air Pollution Control Officer

2. This equipment shall be installed, operated and maintained in strict accord with those recommendations of the manufacturer/supplier and/or sound engineering principles which produce the minimum emissions of contaminants.

3. This unit shall not be operated for more than twelve hours per calendar day.

4. This unit shall only be fired on CARB diesel fuel whose sulfur concentration is less than or equal to 0.05% by weight (500 ppm). As of September 1, 2006 this limit is 0.0015% (15 ppm).

5. A non-resettable four-digit (9,999) hour timer shall be installed and maintained on this unit to indicate elapsed engine operating time.

6. The o/o shall maintain a current operations log for this unit for a minimum of five (5) years, and shall provide the log to District, State or Federal personnel upon request. The log shall include, at a minimum, the information specified below:
 - a. Date of each use, duration of each use (in hours) and location of each use;
 - b. Annual operations in terms of total calendar year fuel consumption (in gallons) or hours;
 - c. Fuel sulfur concentration (the o/o may use the supplier's certification of sulfur content if it is maintained as part of this log).

7. This unit is subject to and must comply with applicable requirements of the Airborne Toxic Control Measure (ATCM) for Diesel Particulate Matter from Portable Engines Rated at 50 Horsepower and Greater (Title 13, CCR 93116). In particular this unit must comply with Title 13 CCR 2423 by January 1, 2010.

8. This unit cannot be operated at the same footprint (spot) for more than 365 consecutive days. [Title 13 CCR 93116.2(bb)]