



MOJAVE DESERT AIR QUALITY MANAGEMENT DISTRICT

14306 Park Avenue Victorville, CA 92392-2310
760.245.1661 -- 800.635.4617 -- FAX 760.245.2022

INACTIVE

B009455

Inactive type Permit has no description information.

EXPIRES LAST DAY OF: DECEMBER 2007

OWNER OF OPERATOR (Co.#629)

Specialty Minerals, Inc
6565 Meridian Road
Lucerne Valley, CA 92356

EQUIPMENT LOCATION (Fac.#262)

Specialty Minerals, Inc
6565 Meridian Road
Lucerne Valley, CA 92356

Description:

GLASS SAND LOADOUT consisting of: a sand handling and transfer system served by a bin vent (C009456).

EQUIPMENT

Capacity	Equipment Description
0	Dust Hoods
40	Dust Hoods Blower

CONDITIONS:

1. Operation of this equipment shall be conducted in accordance with all data and specifications submitted with the application under which this permit is issued otherwise noted below.
2. The owner/operator (o/o) shall maintain this equipment in strict accord with those recommendations of the manufacturer/supplier and/or sound engineering principles which produce the minimum emissions of air contaminants.
3. This unit shall operate concurrently with and shall vent through properly operating baghouse DCL 48 under valid District permit C009456.

Fee Schedule: 1 (a)

Rating: 40 bhp

SIC: 1422

SCC: 30502006

Location/UTM(Km):
508E/3803N

This permit does not authorize the emission of air contaminants in excess of those allowed by law, including Division 26 of the Health and Safety Code of the State of California and the Rules and Regulations of the District. This permit cannot be construed as permission to violate existing laws, ordinances, statutes or regulations of this or other governmental agencies. This permit must be renewed by the expiration date above. If billing for renewal fee required by Rule 301(c) is not received by expiration date above, please contact the District.

Specialty Minerals, Inc
P.O. Box 558
Lucerne Valley, CA 92356

By: **COPY**
Brad Poiriez
Executive Director

4. This equipment shall be operated in compliance with all applicable requirements of 40 CFR 60 Subpart OOO - Standards of Performance for Nonmetallic Mineral Processing Plants.

5. This equipment shall not discharge into the atmosphere an exhaust stream that exhibits greater than the following opacity:

- a. Stack emissions - seven percent (40 CFR 60.672(a))
- b. All transfer points and fugitive emission points - ten percent (40 CFR 60.572(b))

6. The o/o shall conduct an initial compliance test per NSPS Subpart OOO requirements, including PM (USEPA Method 5 or equivalent) and/or opacity (USEPA Method 9 or equivalent) testing as applicable for each baghouse, bin vent and fugitive emission point (transfer point or other) associated with this equipment.

7. Prior to the commencement of construction of this equipment, the o/o shall remove from service baghouse DCL 65 and request cancellation of District Permit C009064 in writing.