



## MOJAVE DESERT AIR QUALITY MANAGEMENT DISTRICT

14306 Park Avenue Victorville, CA 92392-2310  
760.245.1661 -- 800.635.4617 -- FAX 760.245.2022

**INACTIVE**

B013551

Inactive type Permit has no description information.

**EXPIRES LAST DAY OF: JUNE 2020**

### **OWNER OF OPERATOR (Co.#2523)**

Lynx Cat Quarry  
1 Lynx Cat Road  
Hinkley, CA 92347

### **EQUIPMENT LOCATION (Fac.#3925)**

Lynx Cat Quarry  
1 Lynx Cat Road  
Hinkley, CA 92347

### **Description:**

PORTABLE CRUSHING AND SCREENING CIRCUIT consisting of: Equipment to be used as one circuit. If components are used separately, separate District permits are required.

### **EQUIPMENT**

Capacity	Equipment Description
260	Powerscreen Premiertrack 400X Jaw Crusher, DOORS registration TBD
130	Powerscreen S190 Screening Unit, DOORS registration TBD
325	Powerscreen 1000 Maxtrak cone crusher, DOORS registration TBD
111	Powerscreen LL75, DOORS registration TBD

### **CONDITIONS:**

1. This equipment shall be installed, operated and maintained in strict accordance with those recommendations of the manufacturer/supplier and/or sound engineering principles which produce the minimum emissions of contaminants. Unless otherwise noted, this equipment shall also be operated in accordance with all data and specifications submitted with the application for this permit. [District Rules 1302(C)(2)(a)]

Fee Schedule: 1 (c)

Rating: 826 bhp

SIC: 1499

SCC: 30501505

Location/UTM(Km):  
477E/3871N

This permit does not authorize the emission of air contaminants in excess of those allowed by law, including Division 26 of the Health and Safety Code of the State of California and the Rules and Regulations of the District. This permit cannot be construed as permission to violate existing laws, ordinances, statutes or regulations of this or other governmental agencies. This permit must be renewed by the expiration date above. If billing for renewal fee required by Rule 301(c) is not received by expiration date above, please contact the District.

Lynx Cat Quarry  
841 E. Washington Ave B  
  
Santa Ana, CA 92701

By: **COPY**  
**Brad Poiriez**  
Executive Director

2. The maximum hourly throughput of material through this process shall not exceed 149 tons per hour (tph). Exceedance of this limit triggers the requirements of Title 40 CFR 60 subpart OOO - Standards of Performance for Nonmetallic Mineral Processing Plants.

Compliance with this limit shall be verified by condition 7.

[40 CFR 60 Subpart OOO Section 60.670]

3. This plant must be mounted on any chassis or skids and be able to be moved by the application of a lifting or pulling force. In addition, there shall be no cable, chain, turnbuckle, bolt or other means (except electrical connections) by which any piece of equipment is attached or clamped to any anchor, slab, or structure, including bedrock that must be removed prior to the application of a lifting or pulling force for the purpose of transporting the unit.

[40 CFR 60.671]

4. Existing equipment cannot be replaced and/or new equipment cannot be added without submitting an application to the District and receiving a new permit from the District.

[District Rule 201]

5. This equipment shall be powered by line power or an internal combustion diesel engine(s) with a valid District permit and/or DOORS program registration.

[District Rules 1302 and 1320]

6. Throughput from this equipment shall not exceed:

(a) 149 tons/hour

(b) 150 tons/day

(c) 54,750 tons/year in any consecutive 12 month period

Compliance with this limit shall be verified by condition 7.

[40 CFR 60.670 and District Rule 1303]

7. A facility log shall be maintained on-site for at least two (2) years and made available to District personnel upon request. This log shall contain, as a minimum:

(a) Tons of product produced per hour

(b) Tons of product produced per 24 hour day

(c) Tons of product produced per each consecutive twelve-month period

(d) Weekly water spray system inspection records required by condition 9

(e) Maintenance and break down records associated with all water spray systems

(f) Results of all weekly USEPA Method 22 observations required by condition 11.

(g) 12 month rolling average PM10 emissions in ton/year.

[40 CFR 60.670; District Rules 204 and 1302]

8. Water sprays or dust suppression mechanisms/systems shall be used at conveyor points of charge and discharge, crushers, feeders, and screens, to control fugitive emissions. Compliance with this condition shall be verified on a weekly basis per condition 9.

[District Rule 1302 (C)(2)(a)]

9. The owner or operator must perform weekly inspections to verify that high pressure water is properly flowing through all discharge spray nozzles in the wet suppression system. The owner/operator must initiate corrective action within 24 hours and complete corrective action as expeditiously as practical if they find that water is not flowing properly during such inspections. The owner/operator must record each inspection of the water spray nozzles, including the date of each inspection and any corrective actions taken, in the logbook.

[District Rule 1302 (C)(2)(a)]

10. Visible emissions from this equipment shall not exceed an opacity equal to, or greater than, twenty percent (20%) for a period aggregating more than three (3) minutes in any one (1) hour, excluding uncombined water vapor [District Rule 401]. This equipment shall not discharge air contaminants or materials constituting a nuisance to any considerable number of persons or to the public [District Rule 402]

Roadways, work areas and stockpiles shall be kept sufficiently moist to control fugitive dust, and no visible emissions shall extend beyond the property line of the emission source [District Rule 403]. Equipment to properly wet the material being processed shall be maintained in operable condition on-site and used as necessary to assure compliance with this condition.  
[District Rule 1302(C)(2)(a)]

11. The owner/operator must monitor opacity from the property line of this facility on a weekly basis to determine whether visible fugitive dust is crossing the property line in accordance with USEPA Method 22.  
[District Rule 403, USEPA Method 22]

In the event that visible dust is observed crossing the facility's property boundary the system shall be shut down and corrective action must be taken prior to resuming operations.  
[District Rule 403]

12. A facility wide Comprehensive Emission Inventory (CEI) for all emitted criteria and toxic air pollutants must be submitted to the District, in a format approved by the District, upon District request.  
[District Rule 107(b); H&S Code 39607 & 44341-44342; and 40 CFR 51, Subpart A]