

MOJAVE DESERT AIR QUALITY MANAGEMENT DISTRICT

14306 Park AvenueVictorville, CA92392-2310 760.245.1661 -- 800.635.4617 -- FAX760.245.2022

RENEWAL

C001569

Renewal type Permit has no description information.

EXPIRES LAST DAY OF: JUNE 2025

OWNER OF OPERATOR (Co.#1)

CEMEX Construction Materials Pacific LLC 16888 North E Street Victorville,CA92392

EQUIPMENT LOCATION (Fac. #6)

CEMEX - River Plant 16888 North E Street Victorville,CA92392

Description:

BAGHOUSE (LBH-9) consisting of:Dust Collector, General Industrial model Series 20, pulse jet type, with 36 polyester bags, measuring 5 7/8" X 123" each. Filter area is 542 sq ft. air flow is 2450 acfm, at above ambient temperatures (140 deg F), air to cloth ratio is 4.5:1. Induced draft fan motor rated at 7.5 hp. Emissions estimated to 0.01 gr/dscf. Serves Pneumatic Cement Conveyor permitted under B000059 Facility has specified that the normal operating range for pressure differential is between 2 and 5 inches water column.

CONDITIONS:

- 1. The owner/operator (o/o) shall operate this control equipment in strict accord with the manufacturer's specification and/or sound engineering principles.
- 1.The owner/operator (o/o) shall maintain this baghouse in strict accord with those recommendations of the manufacturer/supplier and/or sound engineering principles which produce the minimum emissions of air contaminants.

 [District Rule 204]
- 2. The o/o shall maintain a record of repairs and maintenance on this equipment and submit it to the District on request. The record shall be retained for a minimum period of five years.
- 2. This equipment shall be operated concurrently with Cement Silo 25 covered in District permit B000059. [District Rule 204]

Fee Schedule:7 (h)

Rating:1device

SIC:3241

SCC:30500614

Location/UTM(Km):472E/3823N

This permit does not authorize the emission of air contaminants in excess of those allowed by law, including Division 26 of the Health and Safety Code of the State of California and the Rules and Regulations of the District. This permit cannot be construed as permission to violate existing laws, ordinances, statutes or regulations of this or other governmental agencies. This permit must be renewed by the expiration date above. If billing for renewal fee required by Rule 301(c) is not received by expiration date above, please contact the District.

CEMEX Construction Materials Pacific LLC 16888 North E Street Victorville,CA92392

By: COPY

Brad Poiriez

Air Pollution Control Officer

- 3. The o/o shall maintain on-site, as a minimum, an inventory of replacement bags that assures compliance with applicable Rules of District Regulation IV.
- 3. The o/o shall conduct a minimum program of inspection and maintenance on this equipment, following the operations and maintenance plan requirements pursuant to 40 CFR 63, Subpart LLL. The o/o shall maintain current and on-site for five (5) years a log of the following information, which shall be provided to District personnel upon request:
- a. A site-specific monitoring plan;
- b. Pressure differential across the bags (monthly);
- c. Bags and bag suspension system inspection (quarterly);
- d. Monthly baghouse stack observations using USEPA Method 22 (10-minute test), and USEPA Method 9 (30 minutes of observations) if visible emissions are observed. If no visible emissions are observed for six consecutive months, the frequency can change to semiannually. If no emissions are observed semi-annually the frequency can be changed to annually. If any visible emissions are observed, the frequency reverts to monthly until no visible emissions are observed for six consecutive months.
- e. Date and nature of any system repairs.

[40 CFR 63.1350(f), 1355(g)]

- 4.The o/o shall conduct a minimum program of inspection and maintenance (frequencies may be changed upon successful demonstration to the District that less frequent monitoring is equally effective). The o/o shall maintain current and on-site for five (5) years a log of the following information, which shall be provided to District personnel upon request:
- a. Pressure differential across the bags (monthly);
- b. Baghouse stack visible emissions determination using Method 22 (monthly):
- c. Bags and bag suspension system inspection (quarterly); and
- d. Bag replacements and repairs.
- 4.All equipment shall be operated in compliance with applicable requirements of 40 CFR 63 Subpart LLL National Emission Standard for Hazardous Air Pollutants from the Portland Cement Manufacturing Industry. [40 CFR Part 63 Subpart LLL]
- 5. This baghouse shall discharge no more than 0.18 pounds per hour of PM10 at a maximum concentration of 0.01 gr/dSCF at the operating conditions given in the above description. This equipment does not require a regularly scheduled emission compliance test. However, emission compliance testing may be required at the discretion of the District.
- 5. This baghouse shall not discharge into the atmosphere an exhaust stream that exhibits greater than ten percent opacity. [District Rule 401; 40 CFR 63.1343(b), 1345]
- 6. This equipment shall be operated concurrently with cement silo 25 covered in District permit B000059.
- 6. This baghouse shall discharge no more than 0.18 pounds per hour of PM10 at a maximum concentration of 0.01 gr/dscf of TSP at the operating conditions given in the above description. This equipment does not require a regularly scheduled emission compliance test. However, emission compliance testing may be required at the discretion of the District. [District Rules 204 and 1303]
- 7.The o/o shall maintain on-site, as a minimum, an inventory of replacement bags that assures compliance with applicable Rules of District Regulation IV. [District Rule 204]
- 8.A facility wide Comprehensive Emission Inventory (CEI) for all emitted criteria and toxic air pollutants must be submitted to the District, in a format approved by the District, upon District request. [District Rule 107(b); H&S Code 39607 & 44341-44342; 40 CFR 51, Subpart A]

Permit:C001569 Issue Date:01/22/2025