



MOJAVE DESERT AIR QUALITY MANAGEMENT DISTRICT

14306 Park Avenue Victorville, CA 92392-2310
760.245.1661 -- 800.635.4617 -- FAX 760.245.2022

PERMIT TO OPERATE

C008146

Operation under this permit must be conducted in compliance with all information included with the initial application, initial permit condition, and conditions contained herein. The equipment must be maintained and kept in good operating condition at all times. This Permit to Operate or copy must be posted on or within 8 meters of equipment. If a copy is posted, the original must be maintained on site, available for inspection at all times.

EXPIRES LAST DAY OF: APRIL 2027

OWNER OF OPERATOR (Co.#118)

Mitsubishi Cement Corporation
5808 State Highway 18
Lucerne Valley, CA 92356

EQUIPMENT LOCATION (Fac.#1)

Mitsubishi Cement - Cushenbury Plant
5808 Highway 18
Lucerne Valley, CA 92356

Description:

DUST COLLECTOR FOR SAND PLANT (1-DC-5) consisting of: Mikropul Model 144S-8-20-TR C style baghouse, equipped with an 8" double tipping valve, 144 4 5/8" x 8' bags (1433 sq ft) and fan 1-FA-5 (30 hp) generating 8600 ACFM (air to cloth ratio of 6:1). This baghouse vents screen 1-VS-1, crusher 1-CR-1, screen discharge, crusher discharge, and drops to the picker belt. See diagram 1-F-505.

CONDITIONS:

1. The owner/operator (o/o) shall install, operate and maintain this dust collector in strict accord with those recommendations of the manufacturer/supplier, and sound engineering principles which produce minimum emissions of air contaminants.
2. The o/o will periodically monitor opacity from stack exhaust according to the following methodology:
 - (i) The owner or operator must conduct a monthly 1-minute visible emissions test of each affected source in accordance with USEPA Method 22. The test must be conducted while the affected source is in operation.
 - (ii) If no visible emissions are observed in six consecutive monthly tests for any affected source, the owner or operator may decrease the frequency of testing from monthly to semi-annually for that affected source. If visible emissions are observed during any semi-annual test, the owner or operator must resume testing of that affected source on a monthly basis and maintain that schedule until no visible emissions are observed in six consecutive monthly tests.
 - (iii) If no visible emissions are observed during the semi-annual test for any affected source, the owner or operator may decrease the

Fee Schedule: 7 (h)

Rating: 1 device

SIC: 3241

SCC: 30502006

Location/UTM(Km):
514E/3802N

This permit does not authorize the emission of air contaminants in excess of those allowed by law, including Division 26 of the Health and Safety Code of the State of California and the Rules and Regulations of the District. This permit cannot be construed as permission to violate existing laws, ordinances, statutes or regulations of this or other governmental agencies. This permit must be renewed by the expiration date above. If billing for renewal fee required by Rule 301(c) is not received by expiration date above, please contact the District.

Mitsubishi Cement Corporation
5808 State Highway 18
Lucerne Valley, CA 92356

By: **COPY**
Brad Poiriez
Executive Director

frequency of testing from semi-annually to annually for that affected source. If visible emissions are observed during any annual test, the owner or operator must resume testing of that affected source on a monthly basis and maintain that schedule until no visible emissions are observed in six consecutive monthly tests.

3. The o/o shall log all the items in 2 above in addition to the bag replacements, repairs and non-scheduled maintenance. The log shall be kept current, on-site for a minimum of 5 years and provided to District personnel on request.
4. The o/o shall maintain an inventory of replacement bags on-site at all times which will ensure compliance with applicable Rules of District Regulation IV.
5. The o/o shall install and maintain a device which measures the pressure differential across the bags if one has not been provided with this unit.
6. This baghouse shall operate concurrently with the Sand Plant under valid District permit number B003948.
7. This baghouse shall discharge no more than 0.737 lb/hour at a maximum concentration of 0.01 gr/dscf at the operating conditions described in the above description.
8. The owner/operator (o/o) shall limit the annual operating hours of this baghouse to 6,000 hours per year. Records of monthly and yearly hours of operation shall be kept.
9. This baghouse shall be operated in compliance with all applicable requirements of 40 CFR 60 Subpart OOO - Standards of Performance for Nonmetallic Mineral Processing Plants.
10. This baghouse shall not discharge into the atmosphere an exhaust stream that exhibits greater than seven percent opacity (40 CFR 60.672(a)(2)).