



MOJAVE DESERT AIR QUALITY MANAGEMENT DISTRICT

14306 Park Avenue Victorville, CA 92392-2310
760.245.1661 -- 800.635.4617 -- FAX 760.245.2022

PERMIT TO OPERATE

C010581

Operation under this permit must be conducted in compliance with all information included with the initial application, initial permit condition, and conditions contained herein. The equipment must be maintained and kept in good operating condition at all times. This Permit to Operate or copy must be posted on or within 8 meters of equipment. If a copy is posted, the original must be maintained on site, available for inspection at all times.

EXPIRES LAST DAY OF: JUNE 2025

OWNER OF OPERATOR (Co.#1)

CEMEX Construction Materials Pacific LLC
16888 North E Street
Victorville, CA 92392

EQUIPMENT LOCATION (Fac.#5)

CEMEX - Black Mountain Quarry Plant
25220 Black Mountain Quarry Road
Apple Valley, CA 92307

Description:

BAGHOUSE (FBH2) consisting of: Mikro Pul PulseAire model 221-10-100 TR pulsejet type baghouse with 221 polyester bags, each measuring 4.63" diameter x 42" long. Cloth area is 936 ft², air flow is 12,000 ACFM. Air to Cloth ratio is 12.8:1. Fan motor is rated at 100 hp. Exhaust temperature is 150 F. Unit serves Coal Mill #3 permitted under permit B001083. Facility has specified that the normal operating range for pressure differential is between 1.5 and 5.5 inches water column.

CONDITIONS:

1. The owner/operator (o/o) shall maintain this baghouse in strict accord with those recommendations of the manufacturer/supplier and/or sound engineering principles which produce the minimum emissions of air contaminants.
[District Rule 204, 40 CFR 52.220(c)(39)(ii)(B), 40 CFR 70.6(a)(3)(B)]

1. The owner/operator (o/o) shall maintain this baghouse in strict accord with those recommendations of the manufacturer/supplier and/or sound engineering principles which produce the minimum emissions of air contaminants.
[District Rule 204]

2. This baghouse shall be operated concurrently with coal mill No. 3 (B001083).
[District Rule 204, 40 CFR 52.220(c)(39)(ii)(B), 40 CFR 70.6(a)(3)(B)]

2. This baghouse shall be operated concurrently with Coal Mill No. 3 (B001083).

Fee Schedule: 7 (h)

Rating: 1 device

SIC: 3241

SCC: 30500614

Location/UTM(Km): 476E/3826N

This permit does not authorize the emission of air contaminants in excess of those allowed by law, including Division 26 of the Health and Safety Code of the State of California and the Rules and Regulations of the District. This permit cannot be construed as permission to violate existing laws, ordinances, statutes or regulations of this or other governmental agencies. This permit must be renewed by the expiration date above. If billing for renewal fee required by Rule 301(c) is not received by expiration date above, please contact the District.

CEMEX Construction Materials Pacific
LLC
16888 North E Street
Victorville, CA 92392

By: **COPY**
Brad Poiriez
Air Pollution Control Officer

[District Rule 204]

3.The o/o shall conduct a minimum program of inspection and maintenance on this equipment. The o/o shall maintain current and on-site for five (5) years a log of the following information, which shall be provided to District personnel upon request:

- a. Monthly reading of baghouse pressure drop, date and value;
- b. Monthly (or less frequently if allowed by a 40 CFR 63.1350 operations and maintenance plan) baghouse stack observation date and result (using USEPA Method 22, and USEPA Method 9 if necessary);
- c. Quarterly bag and bag suspension system inspection date and results;
- d. Date of bag replacements; and,
- e. Date and nature of any system repairs.

[District Rule 204, 40 CFR 52.220(c)(39)(ii)(B), 40 CFR 70.6(a)(3)(B)]

3.The o/o shall conduct a minimum program of inspection and maintenance on this equipment, following the operations and maintenance plan requirements pursuant to 40 CFR 63, Subpart LLL. The o/o shall maintain current and on-site for five (5) years a log of the following information, which shall be provided to District personnel upon request:

- a. Monthly reading of baghouse pressure drop, date and value;
- b. Bags and bag suspension system inspection (quarterly);
- c. Monthly baghouse stack observations using USEPA Method 22 (10-minute test), and USEPA Method 9 (30 minutes of observations) if visible emissions are observed. If no visible emissions are observed for six consecutive months, the frequency can change to semi-annually. If no emissions are observed semi-annually the frequency can be changed to annually. If any visible emissions are observed, the frequency reverts to monthly until no visible emissions are observed for six consecutive months.
- d. Date and nature of any system repairs.

[District Rule 204; 40 CFR 60.1350]

4.This baghouse shall be operated in compliance with applicable requirements of 40 CFR 60 Subpart Y - Standards of Performance for Coal Preparation Plants.

[District Rule 204, 40 CFR 60.250]

4.This baghouse shall be operated in compliance with applicable requirements of 40 CFR 60 Subpart Y - Standards of Performance for Coal Preparation Plants.

[District Rule 204; 40 CFR 60.250]

5.This baghouse shall not discharge into the atmosphere an exhaust stream that exhibits greater than twenty percent opacity.

[District Rule 204, 40 CFR 60.252(c)]

5.This baghouse shall not discharge into the atmosphere an exhaust stream that exhibits greater than twenty percent opacity.

[District Rule 401; 40 CFR 60.252(c)]

6.This baghouse shall discharge no more than 1.03 pounds per hour of PM10 at a maximum concentration of 0.01 grains/dscf at the operating conditions given in the above description (BACT). This equipment does not require a regularly scheduled emission compliance test. However, emission compliance testing may be required at the discretion of the District.

[District Rule 204, 40 CFR 52.220(c)(39)(ii)(B), 40 CFR 70.6(a)(3)(B)]

6.This baghouse shall discharge no more than 1.03 pounds per hour of PM10 at a maximum concentration of 0.01 grains/dscf of TSP at the operating conditions given in the above description (BACT). This equipment does not require a regularly scheduled emission compliance test. However, emission compliance testing may be required at the discretion of the District.

[District Rule 204 and 1303]

7.This unit shall be equipped with a device to measure the pressure differential across the bags (manometer).

[District Rule 204, 40 CFR 52.220(c)(39)(ii)(B), 40 CFR 70.6(a)(3)(B)]

7.The owner/operator shall maintain on-site, as a minimum, an inventory of replacement bin socks and filter cartridges that assures

compliance these conditions.
[District Rule 204]

8.The o/o shall maintain on-site a minimum inventory of replacement bags that assures compliance with these conditions.
[District Rule 204, 40 CFR 52.220(c)(39)(ii)(B), 40 CFR 70.6(a)(3)(B)]

8.This unit shall be equipped with a device to measure the pressure differential across the bags (manometer).
[District Rule 204]

9.A facility wide Comprehensive Emission Inventory (CEI) for all emitted criteria and toxic air pollutants must be submitted to the District, in a format approved by the District, upon District request.
[District Rule 107(b); H&S Code 39607 & 44341-44342; 40 CFR 51, Subpart A]