MOJAVE DESERT AIR QUALITY MANAGEMENT DISTRICT
14306 Park Avenue Victorville, CA 92392-2310
760.245.1661 -- 800.635.4617 -- FAX 760.245.2022

RENEWAL

C010858

Renewal type Permit has no description information.

EXPIRES LAST DAY OF: NOVEMBER 2026

OWNER OF OPERATOR (Co.#87)

Commanding Officer, MCLB Barstow, CA
Box 110570 Bldg 196 Attn: Air Program Manager
Barstow, CA 92311-5050

EQUIPMENT LOCATION (Fac.#587)

USMC MCLB - Yermo Annex
USMC Logistics Base
Barstow, CA 923115013

Description:
REGENERATIVE THERMAL OXIDIZER (BLDG 573) consisting of: Munters Zeol System, Model Number IZS-3546-TH; that includes a concentrator (a continuously rotating rotor made of an absorptive medium, zeolite operating in three modes: adsorption, regeneration, and cooling. Also includes one 1,295,000 British thermal units per hour (Btu/hr) burner, natural gas-fired with Eclipse Ratiomatic RM100 Burner set and limited to fire at a rate of 955,052 Btu/hr, heating the combustion chamber to a maximum temperature of 1,450F. Equipment has a stack height of 20 feet and a diameter of 12 inches. Maximum exhaust temperature is 900F; maximum exhaust flow is 1,170 standard cubic feet per minute (scfm). The natural gas low NOx burner is stated by the manufacturer to generate less than 0.15 pounds (lbs) of NOx per million British thermal units (MMBtu). The APCS has been designed for an inlet flowrate of 23,000 scfm with an inlet temperature of 85F. The APCS is guaranteed by the manufacturer to achieve a destruction and removal efficiency of 95 percent. Facility Elevation is 1964 ft above MSL.

CONDITIONS:

1. This equipment shall be operated and maintained in strict accord with the recommendations of its manufacturer or supplier and/or sound engineering principles which produce the minimum emissions of air contaminants. Unless otherwise noted, this equipment shall be operated in compliance with all data and specifications submitted with the application under which this permit is issued.
[District Rule 1302(B)(1)(a)]

2. This thermal oxidizer shall be fully functional and operating whenever the spray booth and curing oven described in District permit S004558 is in use.
[District Rule 1302(B)(1)(a)]

Fee Schedule: 7 (h)	Rating: 1 device	SIC: 9711	SCC: 40299998	Location/UTM(Km): 512E/3861N

This permit does not authorize the emission of air contaminants in excess of those allowed by law, including Division 26 of the Health and Safety Code of the State of California and the Rules and Regulations of the District. This permit cannot be construed as permission to violate existing laws, ordinances, statutes or regulations of this or other governmental agencies. This permit must be renewed by the expiration date above. If billing for renewal fee required by Rule 301(c) is not received by expiration date above, please contact the District.

Commanding Officer, MCLB Barstow, CA
Box 110570 Attn: Air Program Manager
Barstow, CA 92311-5050

By: **COPY**
Brad Poiriez
Executive Director

UNOFFICIAL

3. The owner/operator shall maintain an operations log for this unit current and on-site (or at a central location) for a minimum of five (5) years, and this log shall be provided to District, State and Federal personnel upon request. The log shall include, at a minimum, the information specified below:
a. Results of initial Capture Efficiency source tests;
b. Results of annual Destruction Efficiency demonstrations;
c. Monthly and rolling consecutive twelve month period VOC release records; and
d. Descriptions of all malfunctions and corrective actions taken.
[District Rule 1302(B)(1)(a); 40 CFR 70.6(a)(3)(ii)(b)]

4. The combined emissions from all equipment described in District permits S008392, S008393, S008394, S008395, S008396, S009622, S009969, C008397, C009623, and C009968 (the entire Paint and Undercoat Facility) to the atmosphere shall not exceed 3089 pounds of VOC in any consecutive twelve month period. Compliance with this condition shall be verified through reaction chamber temperature and VOC release records, calibrated with initial capture efficiency source test results and annual destruction efficiency demonstrations.
[District Rules 1302(B)(1)(a), 1115, 1116, and 1303]

5. This equipment shall operate with a control efficiency of 95 percent (capture times destruction), comparing total VOC release in the booths and ovens and actual VOC emissions exhausted to the atmosphere from this device. Compliance tests described below, in conjunction with initial capture efficiency source test results, shall be used to demonstrate this control efficiency.

The owner/operator shall conduct compliance tests at least once every twelve (12) months at the concentrator outlet/oxidizer inlet, oxidizer outlet, and concentrator exhaust to determine VOC concentrations at high VOC loading and corresponding destruction efficiency (over three separate complete concentrator cycles), in accordance with the MDAQMD Compliance Test Procedural Manual. VOC concentrations shall be determined in accordance with USEPA Test Methods 25, 25A, or 25B, with USEPA Test Method 18, or CARB Method 422 used to determine exempt compound concentrations.

VOC concentrations in the concentrator exhaust shall be less than 10 ppm as methane. VOC emissions to the atmosphere shall be determined as the sum of emissions from the oxidizer outlet and concentrator exhaust. The concentrator exhaust flow rate shall be assumed as the sum of maximum design flow rates from all connected spray booths if not measured as part of the compliance test procedures.

Compliance Test Notifications, Protocols, and Results:
a. The owner/operator must submit a compliance/source test protocol at least thirty (30) days prior to the compliance/source test date. The owner/operator must conduct all required compliance/certification tests in accordance with a District-approved test protocol.
b. The owner/operator must notify the District a minimum of ten (10) days prior to the compliance/source test date so that an observer may be present.
c. The final compliance/source test results must be submitted to the District within forty-five (45) days of completion of the test.
d. All compliance/source test notifications, protocols, and results may be submitted electronically to reporting@mdaqmd.ca.gov.
[Rule 1302(B)(1)(a)]

6. This thermal oxidizer shall only use PUC-regulated pipeline quality natural gas for fuel.
[District Rule 1303]

7. A facility-wide Comprehensive Emission Inventory (CEI) for all emitted criteria and toxic air pollutants must be submitted to the District, in a format approved by the District, upon District request.
[Rule 107(b), HSC 39607 and 44341-44342, 40 CFR 51, Subpart A]