



MOJAVE DESERT AIR QUALITY MANAGEMENT DISTRICT

14306 Park Avenue Victorville, CA 92392-2310
760.245.1661 -- 800.635.4617 -- FAX 760.245.2022

INACTIVE

C011947

Inactive type Permit has no description information.

EXPIRES LAST DAY OF: JUNE 2017

OWNER OF OPERATOR (Co.#1)

CEMEX Construction Materials Pacific LLC
16888 North E Street
Victorville, CA 92392

EQUIPMENT LOCATION (Fac.#6)

CEMEX - River Plant
16888 North E Street
Victorville, CA 92392

Description:

AFSC SYSTEM BAGHOUSE - 3 consisting of: Alternative Fuels - Storage Hall and Conveyance System Baghouse with a Design Gas Flow rate of 2800 cubic feet per minute. Total number of filters is 1; material is Polyester Felt 16 oz; length is; 27 inch CARTRIDGE; diameter is 4 inches; serves AFSC system Permitted as B011678.

CONDITIONS:

1. This baghouse shall be operated in compliance with applicable requirements of 40 CFR 60 Subpart F - Standards of Performance for Portland Cement Plants and 40 CFR 63 Subpart LLL - National Emission Standard for Hazardous Air Pollutants From the Portland Cement Manufacturing Industry. [Rule 204]
2. This baghouse shall not discharge into the atmosphere an exhaust stream that exhibits greater than ten percent opacity [40 CFR Part 63 Subpart LLL Section 63.1345].
3. This baghouse shall not discharge PM10 in excess of 0.005 grains/dscf (BACT) at the operating conditions given in the above description. [Rule 1302]
4. The o/o shall conduct a minimum program of inspection and maintenance on this equipment. The o/o shall maintain current and on-site for five (5) years a log of the following information, which shall be provided to District, State or Federal personnel upon request:
 - a. Weekly reading of baghouse pressure drop, date and value;
 - b. Quarterly bag and bag suspension system inspection date and results;
 - c. Date of bag replacements;

Fee Schedule: 7 (h)

Rating: 1 device

SIC: 3241

SCC: 30500606

Location/UTM(Km):
472E/3823N

This permit does not authorize the emission of air contaminants in excess of those allowed by law, including Division 26 of the Health and Safety Code of the State of California and the Rules and Regulations of the District. This permit cannot be construed as permission to violate existing laws, ordinances, statutes or regulations of this or other governmental agencies. This permit must be renewed by the expiration date above. If billing for renewal fee required by Rule 301(c) is not received by expiration date above, please contact the District.

CEMEX Construction Materials Pacific
LLC
16888 North E Street
Victorville, CA 92392

By: **COPY**
Eldon Heaston
Air Pollution Control Officer

- d. Date and nature of any system repairs; and,
- e. Average PM emissions in lb/ton of clinker per Condition 12 (Not To Exceed 0.10 until September 9, 2015 when the PM shall Not Exceed 0.07); NOTE AVERAGE NEEDS TO BE DEFINED.
[Rule 1302]
5. This equipment shall be installed, operated and maintained in strict accordance with those recommendations of the manufacturer which produce the minimum emissions of contaminants. Unless otherwise noted, this equipment shall also be operated in accordance with all data and specifications submitted with the application for this permit. [Rule 204]
6. The owner/operator shall maintain a record of repairs and maintenance on this equipment and submit it to the District, State, or Federal personal upon request. The record shall be retained for a minimum period of five (5) years. [Rule 204]
7. This air pollution control device shall be fitted with an operating air lock system on each material discharge port and shall be provided with a differential pressure measuring device. The nominal design operational/differential pressure range shall be maintained in accordance with manufacturer's recommendations and/or good engineering practices. [Rule 1302]
8. The owner/operator shall maintain on-site, as a minimum, an inventory of replacement bags/filters that assures compliance these conditions. [Rule 1302]
9. This air pollution control device shall discharge no more than 2.88 pounds per hour of PM10 at a maximum concentration of 0.005 grains/dscf at the operating conditions given in the above description. To demonstrate compliance with this condition, the owner/operator shall maintain the manufacturer's data guaranteeing the grain loading of this dust collector.
[Rule 1303 - NSR Requirements]
10. No Later than September 9, 2015, PM shall be continuously monitored with a properly functioning PM Monitor maintained and calibrated in accordance with manufacturers requirements and the requirements of subsection 63.1350(f)(4)(i). [Rule 1302]
11. This baghouse shall be equipped with a properly functioning Continuous Opacity Monitor (COM) that is installed, maintained and calibrated per manufacturer s recommendations. COM opacity shall not exceed 10% opacity at any time. [40 CFR 63 Subpart LLL]
12. An initial and annual PM performance test performed in accordance with EPA Method 5 or 5I consisting of three 1-hr tests shall be conducted within 90 days of this equipment becoming operational and annually thereafter. This condition is NOT required once the PM monitor is installed and operating properly. [Rule 204]
13. This equipment shall not be operated until the road paving project at the River Plant is complete as the emissions from this equipment has been offset by simultaneous emission reductions (SERS) from the road paving project at the main entrance roadway; this project is 2370 feet long by 30 feet wide. [Rule 204; Rule 1303]
14. This Baghouse is subject to District Rules and Regulations and the Cement NESHAP 40 CFR 63 Subpart LLL. In the event of conflict the more stringent requirements shall govern. [Rule 204]