

emissions are observed frequency reverts to monthly until no visible emissions are observed for six consecutive months;
(c) Annual bag and bag suspension system inspection date and results;
(d) Date of bag replacements; and,
(e) Date and nature of any system repairs.
[District Rule 1203(D)(1)(d)(ii), 1303(A); 40 CFR 63.1350(f), 1355(g)]

4.This baghouse shall be operated in compliance with applicable requirements of 40 CFR 63 Subpart LLL - National Emission Standard for Hazardous Air Pollutants from the Portland Cement Manufacturing Industry.
[40 CFR Part 63 subpart LLL]

5.This baghouse shall not discharge into the atmosphere an exhaust stream that exhibits greater than ten percent opacity.
[District Rule 401; 40 CFR 63.1345]

6.This baghouse shall discharge no more than 0.6 pounds per hour of PM10 at a maximum concentration of 0.005 grains/dscf at the operating conditions given in the above description (BACT). This equipment does not require a regularly scheduled emission compliance test. However, emission compliance testing may be required at the discretion of the District.
[District Rules 1303(A), 404, 405]

7.This unit shall be equipped with a device to measure the pressure differential across the bags (manometer).
[District Rule 1303(A)]

8.The o/o shall maintain on-site a minimum inventory of replacement bags that assures compliance with these conditions.
[District Rule 1303(A)]