



## MOJAVE DESERT AIR QUALITY MANAGEMENT DISTRICT

14306 Park Avenue Victorville, CA 92392-2310  
760.245.1661 -- 800.635.4617 -- FAX 760.245.2022

**INACTIVE**

**B007559**

Inactive type Permit has no description information.

**EXPIRES LAST DAY OF: DECEMBER 2000**

### **OWNER OF OPERATOR (Co.#9)**

Searles Valley Minerals Operations, Inc  
13200 Main Street  
Trona, CA 93562

### **EQUIPMENT LOCATION (Fac.#2)**

SVM - Trona Plant  
13200 Main Street  
Trona, CA 93562

#### **Description:**

PYRO FLUX HANDLING SYSTEM consisting of: Pyro flux screening and handling equipment located within the potash storage building. This process train will handle a maximum of 100 tons per month of pyro flux. This permit also covers the potential fugitive emissions associated with the pyro flux handling system.

#### **EQUIPMENT**

Capacity	Equipment Description
0	Receiving Hopper
3	Incline Conveyor Belt (18" x 60')
3	Scalping Screen
0	Tote Filler
15	Screw Conveyor
15	Bucket Elevator
7.5	Transfer Belt #1 (18" x 30')
20	Transfer Belt #2 (24" x 120')
1	Loading Spout

#### **CONDITIONS:**

1. This system shall not receive more than 1200 tons of pyro flux in any calendar year.

Fee Schedule: 1 (b)

Rating: 64.5bhp

SIC: 1474

SCC: 99999999

Location/UTM(Km): 466E/3957N

This permit does not authorize the emission of air contaminants in excess of those allowed by law, including Division 26 of the Health and Safety Code of the State of California and the Rules and Regulations of the District. This permit cannot be construed as permission to violate existing laws, ordinances, statutes or regulations of this or other governmental agencies. This permit must be renewed by the expiration date above. If billing for renewal fee required by Rule 301(c) is not received by expiration date above, please contact the District.

Searles Valley Minerals Operations, Inc  
P.O. Box 367  
Trona, CA 93592-0367

By: **COPY**  
**Brad Poiriez**  
Air Pollution Control Officer

2.This equipment shall comply with all applicable requirements of the Standards of Performance for Nonmetallic Mineral Processing Plants (40 CFR 60 Subpart OOO).

3.This equipment shall not emit from any conveyor transfer point or other fugitive source (except truck dumping) emissions which exceed 10 percent opacity, determined using Method 9 as modified by 40 CFR 60.675(c).

4.The building enclosing this equipment shall not discharge visible emissions.

5.The owner/operator shall log the amount of pyro flux received by this equipment and the results of all opacity and visible emissions observations. This log shall be maintained current and on-site for a minimum of five (5) years and shall be provided to District personnel on request.

6.This equipment shall be operated and maintained in strict accord with the recommendations of its manufacturer or supplier and/or sound engineering principles.