



MOJAVE DESERT AIR QUALITY MANAGEMENT DISTRICT

14306 Park Avenue Victorville, CA 92392-2310
760.245.1661 -- 800.635.4617 -- FAX 760.245.2022

AUTHORITY TO CONSTRUCT

C011940

If construction is not completed by the expiration date of this permit, it may be renewed for one additional year upon payment of applicable fees. Any additional extension will require the written approval of the Air Pollution Control Officer. This Authority to Construct may serve as a temporary Permit to Operate provided the APCO is given prior notice of intent to operate and the Permit to Operate is not specifically denied.

EXPIRES LAST DAY OF: JUNE 2026

OWNER OF OPERATOR (Co.#1)

CEMEX Construction Materials Pacific LLC
16888 North E Street
Victorville, CA 92392

EQUIPMENT LOCATION (Fac.#5)

CEMEX - Black Mountain Quarry Plant
25220 Black Mountain Quarry Road
Apple Valley, CA 92307

Description:

CKD HANDLING SYSTEM COLLECTION HOPPER - BAGHOUSE consisting of: CKD Handling System Baghouse with a Design Gas Flow rate of 1750 cubic feet per minute. Total number of filters is 49; material is POLYIMIDE (P84); length is 8 feet; diameter is 6.088 inches. Serves CKD Handling System (B011939). Facility has specified that the normal operating range for pressure differential is between 1 and 5 inches water column.

CONDITIONS:

1. The owner/operator (o/o) shall maintain this baghouse in strict accord with those recommendations of the manufacturer/supplier and/or sound engineering principles which produce the minimum emissions of air contaminants.

[District Rule 204]

2. This baghouse shall operate concurrently with CKD Handling System under District Permit B011939.

[District Rule 204]

3. The o/o shall conduct a minimum program of inspection and maintenance on this equipment, following the operations and maintenance plan requirements pursuant to 40 CFR 63, Subpart LLL. The o/o shall maintain current and on-site for five (5) years a log of the following information, which shall be provided to District personnel upon request:

- A site-specific monitoring plan;
- Monthly reading of baghouse pressure drop, date and value;
- Bags and bag suspension system inspection (quarterly);
- Monthly baghouse stack observations using USEPA Method 22 (10-minute test), and USEPA Method 9 (30 minutes of observations)

Fee Schedule: 7 (h)

Rating: 1 device

SIC: 3241

SCC: 30500718

Location/UTM(Km): 476E/3826N

This permit does not authorize the emission of air contaminants in excess of those allowed by law, including Division 26 of the Health and Safety Code of the State of California and the Rules and Regulations of the District. This permit cannot be construed as permission to violate existing laws, ordinances, statutes or regulations of this or other governmental agencies. This permit must be renewed by the expiration date above. If billing for renewal fee required by Rule 301(c) is not received by expiration date above, please contact the District.

CEMEX Construction Materials Pacific
LLC
16888 North E Street
Victorville, CA 92392

By: **COPY**

Brad Poiriez

Air Pollution Control Officer

if visible emissions are observed. If no visible emissions are observed for six consecutive months, the frequency can change to semi-annually. If no emissions are observed semi-annually the frequency can be changed to annually. If any visible emissions are observed, the frequency reverts to monthly until no visible emissions are observed for six consecutive months.

e. Date and nature of any system repairs

f. Average PM emissions in lb/ton of clinker per Condition 10;

[District Rule 1302]

4.The systems air pollution control devices shall be fitted with an operating air lock system on each material discharge port and shall be provided with a differential pressure measuring device. The nominal design operational/differential pressure range shall be maintained in accordance with manufacturer's recommendations and/or good engineering practices.

[District Rule 1302]

5.This System shall be operated in compliance with applicable requirements of 40 CFR 60 Subpart F - Standards of Performance for Portland Cement Plants and 40 CFR 63 Subpart LLL - National Emission Standard for Hazardous Air Pollutants From the Portland Cement Manufacturing Industry.

[District Rule 204]

6.System dust collectors shall not discharge into the atmosphere an exhaust stream that exhibits greater than ten percent opacity.

[40 CFR 63.1343(b), 1345]

7.This air pollution control device shall discharge no more than 2.14 pounds per hour of PM10 at a maximum concentration of 0.005 grains/dscf of TSP at the operating conditions given in the above description. To demonstrate compliance with this condition, the owner/operator shall maintain the manufacturer's data guaranteeing the grain loading of this dust collector.

[District Rule 1302]

8.Emissions from this equipment have been offset by simultaneous emission reductions (SER's) from the road paving project at the Quarry Plant main entrance roadway. Road center line is defined as: from lat/long of 34.622956/-117.101988 to a lat/long of 34.619300/-117.103491; this project is 1774 feet long by 39 feet wide. This road shall be maintained in good order, free from pot holes and excessive dirt as to minimize fugitive particulate emissions.

[District Rules 204, 1302, 1303 and 1305]

9.The owner/operator shall maintain on-site, as a minimum, an inventory of replacement bin socks and filter cartridges that assures compliance these conditions.

[District Rule 204]

10.Pursuant to 40 CFR part 63 subpart LLL, PM emissions from this CKD baghouse shall not exceed 0.07 lb/ton of clinker.

[40 CFR part 63 subpart LLL section 63.1343]

11.A facility wide Comprehensive Emission Inventory (CEI) for all emitted criteria and toxic air pollutants must be submitted to the District, in a format approved by the District, upon District request.

[District Rule 107(b); H&S Code 39607 & 44341-44342; 40 CFR 51, Subpart A]