



MOJAVE DESERT AIR QUALITY MANAGEMENT DISTRICT

14306 Park Avenue Victorville, CA 92392-2310
760.245.1661 -- 800.635.4617 -- FAX 760.245.2022

INACTIVE

C013342

Inactive type Permit has no description information.

EXPIRES LAST DAY OF: JUNE 2025

OWNER OF OPERATOR (Co.#2500)

5E Boron Americas, LLC
9329 Mariposa Rd. Suite # 210
Hesperia, CA 92344

EQUIPMENT LOCATION (Fac.#3893)

5E Boron Americas, LLC
27555 Hector Road
Newberry Springs, CA 92365

Description:

BAGHOUSE, BA DRYER #2 consisting of: A Sly, Inc. model STJ-46-8 pulsejet style baghouse equipped with 24 fabric filters, each measuring 8 feet tall by 5.75 inches in diameter, yielding a total cloth area of 289 square feet. Nominal flow is approximately 1120 acfm via an induced flow fan motor rated at 7.5 bhp, yielding an air to cloth ratio of 3.9:1. The pressure differential range is from 0.5 to 8.0 inches water column and the maximum outlet grain loading is 0.50 mg/m³ (0.022 gr/scf).

CONDITIONS:

1. This equipment shall be installed, operated and maintained in strict accordance with those recommendations of the manufacturer/supplier and/or sound engineering principles which produce the minimum emissions of contaminants. Unless otherwise noted, this equipment shall also be operated in accordance with all data and specifications submitted with the application for this permit. [District Rule 1302]

2. A manometer shall be installed to indicate the pressure differential across the filters. Furthermore, the pressure differential shall be maintained between 0.5 and 8.0 inches water column. [District Rules 1302 and 1303]

3. This baghouse shall be fully functional and operating whenever the Boric Acid dryer described in District Permit B013322 is operating. [District Rules 1302, 1303 and 1320]

4. Visible emissions from this equipment shall not exceed an opacity equal to, or greater than, twenty percent (20%) for a period aggregating more than three (3) minutes in any one (1) hour, excluding uncombined water vapor [District Rule 401]. This equipment shall not discharge air contaminants or materials constituting a nuisance to any considerable number of persons or to the public [District Rule 402]. Roadways, work areas and stockpiles shall be kept sufficiently moist to control fugitive dust, and no visible emissions shall

Fee Schedule: 7 (h)

Rating: 1 device

SIC: 1479

SCC: 30510098

Location/UTM(Km): 552E/3846N

This permit does not authorize the emission of air contaminants in excess of those allowed by law, including Division 26 of the Health and Safety Code of the State of California and the Rules and Regulations of the District. This permit cannot be construed as permission to violate existing laws, ordinances, statutes or regulations of this or other governmental agencies. This permit must be renewed by the expiration date above. If billing for renewal fee required by Rule 301(c) is not received by expiration date above, please contact the District.

5E Boron Americas, LLC
9329 Mariposa Rd. Suite # 210
Hesperia, CA 92344

By: **COPY**
Brad Poiriez
Air Pollution Control Officer

extend beyond the property line of the emission source [District Rule 403]. Equipment to properly wet the material being processed shall be maintained in operable condition on-site and used as necessary to assure compliance with this condition [District Rules 401, 402, 403, and 1302(C)(2)(a)]

5. The owner/operator will periodically monitor opacity from fugitive emission points according to the following methodology:

- a. The owner or operator must conduct a monthly 6-minute visible emissions test on each transfer and drop point in accordance with USEPA Method 22. The test must be conducted while the affected source is in operation.
 - b. If no visible emissions are observed in six consecutive monthly tests for any transfer or drop point, the owner or operator may decrease the frequency of testing from monthly to semi-annually for that transfer or drop point. If visible emissions are observed during any semi-annual test, the owner or operator must resume testing of that transfer or drop point on a monthly basis and maintain that schedule until no visible emissions are observed in six consecutive monthly tests.
 - c. If no visible emissions are observed during two consecutive semi-annual test for any transfer or drop point, the owner or operator may decrease the frequency of testing from semi-annually to annually for that transfer or drop point. If visible emissions are observed during any annual test, the owner or operator must resume testing of that transfer or drop point on a monthly basis and maintain that schedule until no visible emissions are observed in six consecutive monthly tests.
- [District Rules 401, 402, 403, and 1302(C)(2)(a)]

In the event that opacity is observed during the USEPA Method 22, the owner/operator must do one of the following:

- a. Conduct a USEPA Method 9 to determine compliance with the opacity limit this condition. If the opacity limit of this condition is not violated, the owner/operator must ensure that all equipment and controls are operating correctly, but operations are not required to be shut down. If the opacity limit of condition #4 is violated the owner/operator must adhere to option 'b.' below.
- b. Shut down the affected equipment and take corrective action to preclude any further emissions. Upon restarting the affected equipment, the owner/operator must conduct a USEPA Method 22 and/or Method 9 to demonstrate that the corrective action taken was sufficient. Equipment breakdowns resulting in violation and/or shutdown shall be reported to the District in accordance with District Rule 430.

[District Rules 403 and 430]

6. The owner/operator shall conduct quarterly inspections of the bags, the bag suspension system, and the pulsing system to ensure there are no holes in the bags and the suspension and pulsing systems are functioning properly.

[District Rule 1302]

7. Emissions from the entire facility shall not exceed the following limits:

- a. Oxides of Nitrogen (NO_x): 24 tons per consecutive twelve month period, measured as NO₂;
- b. Oxides of Sulfur (SO_x): 24 tons per consecutive twelve month period;
- c. Volatile Organic Compounds (VOC): 24 tons per consecutive twelve month period;
- d. Carbon Monoxide (CO): 95 tons per consecutive twelve month period;
- e. Hydrogen Sulfide (H₂S): 9.5 tons per consecutive twelve month period;
- f. Lead (Pb): 0.5 tons per consecutive twelve month period;
- g. Particulate Matter 10 microns and less (PM₁₀): 14.5 tons per consecutive twelve month period;
- h. Any single Hazardous Air Pollutant (HAP): 9.5 tons per consecutive twelve month period; and
- i. All HAPs combined: 24 tons per consecutive twelve month period.

Compliance shall be demonstrated to the District through the submission of a District approved Comprehensive Emission Inventory Report (CEI) or other equivalent and District approved method.

[District Rules 1302 and 1320]

8. In the event of a malfunction of any emissions related part of this baghouse, the associated Boric Acid dryer must be shut down as soon as safely possible and shall not be restarted until all malfunctions have been corrected. Equipment breakdowns shall be reported to the District in accordance with District Rule 430.

[District Rules 430 and 1302]

9. The owner/operator must maintain an operations log for this equipment. This log shall be maintained current, kept for a total of five (5) years and be provided to authorized personnel upon request. The log shall contain the following at a minimum:

- a. Weekly pressure differential readings done during normal operations, in inches of water column.
- b. Results of all opacity checks as required by Condition #5;
- c. Results of all Quarterly system inspections as required by Condition #6; and
- d. Times and durations of malfunctions, a description of each malfunction, and the corrective action taken for each malfunction.

[District Rules 401 and 1302]

10.A facility wide Comprehensive Emission Inventory (CEI) for all emitted criteria and toxic air pollutants must be submitted to the District, in a format approved by the District, upon District request.
[District Rule 107(b), H&S Code 39607 & 44341-44342, and 40 CFR 51, Subpart A]