



MOJAVE DESERT AIR QUALITY MANAGEMENT DISTRICT

14306 Park Avenue Victorville, CA 92392-2310
 760.245.1661 -- 800.635.4617 -- FAX 760.245.2022

AUTHORITY TO CONSTRUCT

C014254

If construction is not completed by the expiration date of this permit, it may be renewed for one additional year upon payment of applicable fees. Any additional extension will require the written approval of the Air Pollution Control Officer. This Authority to Construct may serve as a temporary Permit to Operate provided the APCO is given prior notice of intent to operate and the Permit to Operate is not specifically denied.

EXPIRES LAST DAY OF: FEBRUARY 2027

OWNER OF OPERATOR (Co. #2349)

MP Mine Operations LLC
 67750 Bailey Road
 Mountain Pass, CA 92366

EQUIPMENT LOCATION (Fac. #364)

Mountain Pass Mine
 67750 Bailey Road
 Mountain Pass, CA 92366

Description:

LEACH CAUSTIC SCRUBBER consisting of: Bionomic Industries Series 5000 Model 136 Packed Tower. 72 inch dia. x 25' high, 850 gallon.

EQUIPMENT

Capacity	Equipment Description
0	531-D20-STK601 Leach Caustic Scrubber Exhaust Stack
0	531-D20-SSE600 Leach Caustic Scrubber
0	531-D20-P601 Leach Caustic Scrubber Circulation Pump A
0	531-D20-P602 Leach Caustic Scrubber Circulation Pump B
0	531-D20-P607 Leach Caustic Scrubber Hydrogen Peroxide Pump A
0	531-D20-P608 Leach Caustic Scrubber Hydrogen Peroxide Pump B
0	531-D20-BL601 Leach Caustic Scrubber Blower A
0	531-D20-BL602 Leach Caustic Scrubber Blower B
0	531-D20-TK601 Leach Caustic Scrubber Discharge Surge Tank
0	531-D20-P603 Bleach Removal Tank #1 Pump A
0	531-D20-P604 Bleach Removal Tank #1 Pump B

Fee Schedule: 7 (h)

Rating: 1 device

SIC: 1099

SCC: 39999989

Location/UTM(Km):
634E/3926N

This permit does not authorize the emission of air contaminants in excess of those allowed by law, including Division 26 of the Health and Safety Code of the State of California and the Rules and Regulations of the District. This permit cannot be construed as permission to violate existing laws, ordinances, statutes or regulations of this or other governmental agencies. This permit must be renewed by the expiration date above. If billing for renewal fee required by Rule 301(c) is not received by expiration date above, please contact the District.

MP Mine Operations LLC
 1700 S. Pavilion Center Drive, 8th Floor
 Las Vegas, NV 89135

By: **COPY**
Brad Poiriez
 Executive Director

CONDITIONS:

1. This equipment shall be installed, operated and maintained in strict accordance with those recommendations of the manufacturer/supplier and/or sound engineering principles which produce the minimum emissions of contaminants. Unless otherwise noted, this equipment shall also be operated in accordance with all data and specifications submitted with the application for this permit. [District Rule 1302]

2. This equipment shall control emissions from and be operated concurrent with the Leach Thickening and Filtration System under valid District permit B014255 and the Hard Leach Venturi Scrubber under permit C012086. [District Rules 1302 and 1320]

3. This scrubber shall not exceed the following limits:

a. 0.300 lb/hour (outlet) chlorine;

b. the less stringent of: 1 ppmv HCl (outlet) or 97% control efficiency

Emissions/control efficiency shall be verified by an initial source test to be conducted within 180 days of start up in accordance with the Districts Compliance Test Procedural Manual. No less than 30 days prior to the proposed test date a written protocol shall be submitted for review and approval. No less than 10 days prior to the proposed test date written notification of test date shall be submitted to the District. No later than 45 days after the test is performed, a written test report shall be submitted. All documents pertaining to the referenced source test shall be submitted to reporting@mdaqmd.ca.gov.

[District Rule 1520]

4. A pH meter shall be installed to indicate the pH of the NaOH scrubbant. Furthermore, the pH shall be maintained between 10.0 and 14.0 and the meter shall be calibrated at least quarterly in accordance with the manufacturer's procedures.

[District Rules 1302 and 1303]

5. A flow meter, of appropriate range, shall be installed and maintained (including calibration) in accordance with manufacturers specification. The flow meter shall be installed such that measurements reflect the scrubbant recirculation flow.

[District Rule 1302]

6. When in operation, the minimum scrubbant recirculation flow rate is 200 GPM and the scrubber pressure drop shall be maintained between 0 and 10 inches water column. Scrubbant recirculation flow rate and pressure drop shall be recorded daily.

[District Rule 1302]

7. This equipment does not require regular emissions testing however testing may be required at District discretion.

[District Rule 1320]

8. In the event of a malfunction of any emissions related part of this scrubber, the Leach Thickening and Filtration System under District permit B014255 must be shut down as soon as safely possible and shall not be restarted until all malfunctions have been corrected. Equipment breakdowns shall be reported to the District in accordance with District Rule 430.

[District Rules 430 and 1302]

9. The owner/operator must maintain an operations log for this equipment. This log shall be maintained current, kept for a total of five (5) years and be provided to authorized personnel upon request. The log shall contain the following at a minimum:

a. Daily scrubbant pH readings;

b. Dates and results of all quarterly pH meter calibrations as required by Condition #4;

c. Daily pressure differential recording;

d. Daily scrubbant recirculation flow meter recording as required by Condition #6;

e. Annual inspection of spray nozzle(s) and spray nozzle system;

f. Dates and description of maintenance, repairs/replacements performed; and,

g. Times and durations of malfunctions, a description of each malfunction, and the corrective action taken for each malfunction. [District Rules 401 and 1302]

10. Actual emissions from this facility shall be less than the following:

- a. 42 tons per year of NO_x [Rule 1303(B)]
- b. 46 tons per year of PM₁₀ [Rule 1303(B)]
- c. 25 tons per year of VOC
- d. 25 tons per year of SO_x
- e. 100 tons per year of CO, calculated on a rolling twelve-month basis
- f. 10 tons per year for any single HAP and 25 tons per year for any combination of HAPs calculated on a rolling twelve-month basis. HAPs are defined in 40 CFR 61.01 and are the chemical compounds listed in section 112(b) of the Clean Air Act (Act). Compliance with the annual emission limits shall be demonstrated via 12 month rolling sum for CO and HAP via annual emission inventory reports for all criteria pollutants and HAP.

[District Rule 1303]

11. A facility wide Comprehensive Emission Inventory (CEI) for all emitted criteria and toxic air pollutants must be submitted to the District, in a format approved by the District, upon District request.

[District Rule 107(b); H&S Code 39607 & 44341-44342; and 40 CFR 51, Subpart A]