



**MOJAVE DESERT AIR QUALITY MANAGEMENT DISTRICT**

14306 Park Avenue Victorville, CA 92392-2310  
760.245.1661 -- 800.635.4617 -- FAX 760.245.2022

**INACTIVE**

P007342

Inactive type Permit has no description information.

**EXPIRES LAST DAY OF: MAY 2012**

**OWNER OF OPERATOR (Co.#1265)**

National Environmental Fiberglass, LLC  
9444 Cassia Rd  
Adelanto, CA 92301

**EQUIPMENT LOCATION (Fac.#2186)**

National Environmental Fiberglass - Adelanto  
9444 Cassia Road  
Adelanto, CA 92301

**Description:**

FIBERGLASS SPRAY GUN consisting of: Glas-Craft Model LPA II AAC Gel-Coat, Wet-Out, and B-410 Chopper System, SN 0001; SP-85 Catalyst Slave Pump, 18913-00 Material Pump, Cart, Mast, and Boom..

**CONDITIONS:**

1. The total amount of VOC and/or organic solvents as defined in Rule 102 that can be released to the atmosphere from this facility shall not exceed 49,800 pounds (24.9 tons) per rolling twelve calendar month period.
2. The total amount of photochemically reactive organic solvents that may be released by this facility to the atmosphere shall not exceed 39.6 lbs/day.
3. This spray gun and the entire facility shall be maintained and operated in compliance with USEPA NESHAP Maximum Achievable Control Technology (MACT) Standards found in 40 CFR 63 Subparts A and WWWW to include but not limited to the following:
  - a. The open molding HAP emissions shall not exceed the HAP emission limits in Table 3 or Table 7, depending on which compliance option is chosen to demonstrate compliance with Subpart WWWW of 40 CFR 63. In accordance with Subpart 63.5810, the facility may use Option A in 63.5810(a), Option B in 63.5810(b), Option C in 63.5810(c), or Option D in 63.5810(d) to comply with the open molding limits.
  - b. HAP emissions (commonly styrene and methyl methacrylate) shall be determined by using the equations found in Table 1 of Subpart WWWW to 40 CFR 63.

Fee Schedule: 7 (c)

Rating: 1 device

SIC: 3564

SCC: 30800722

Location/UTM(Km):  
459E/3826N

This permit does not authorize the emission of air contaminants in excess of those allowed by law, including Division 26 of the Health and Safety Code of the State of California and the Rules and Regulations of the District. This permit cannot be construed as permission to violate existing laws, ordinances, statutes or regulations of this or other governmental agencies. This permit must be renewed by the expiration date above. If billing for renewal fee required by Rule 301(c) is not received by expiration date above, please contact the District.

National Environmental Fiberglass, LLC  
9444 Cassia Rd  
Adelanto, CA 92301

By: **COPY**  
**Eldon Heaston**  
Air Pollution Control Officer

c. This facility must comply with Work Practices found in Table 4 to Subpart WWWW of 40 CFR 63 and demonstrate compliance with these Work Practices per Table 9 to Subpart WWW of 40 CFR 63.

d. This facility must submit semi-annual Compliance Reports as required in Table 14 to Subpart WWWW of 40 CFR 63 per 40 CFR 63.5910(b) on or before January 31 and July 31 of each year.

e. This facility is required to meet operation and maintenance requirements 40 CFR 63.6(e)(1) and (2).

f. This facility must submit a Notification of Compliance Status per 40 CFR 63.9(h) and Table 13 to Subpart WWWW of 40 CFR 63.

g. In the event of conflict between the MACT Standard, and the conditions cited below, the MACT standard shall govern.

4. The owner/operator shall maintain a log for the facility, which, at a minimum, contains the information specified below. This log shall be maintained for a minimum five (5) years, available on site for a minimum of two years, and shall be provided to District personnel on request:

a. Date of operation;

b. Manufacturer, type, and amount (in pounds or gallons) of resin, coating and solvent used (preparation, thinning, cleanup or other);

c. VOC content of each type of resin, coating and solvent in pounds per gallon or grams per liter or percent (weight/weight);

d. Photochemically reactive organic solvent and organic solvent content of each type of resin, coating and solvent in pounds per gallon or grams per liter or percent (weight/weight);

e. Keep daily records of VOC containing material and/or organic solvents used;

f. Total amount of VOC and/or organic solvents used per calendar month;

g. Total amount of photochemically reactive organic solvents used per day.

5. This equipment shall only be operated/maintained in strict accord with manufacturer's/supplier's recommendations and/or sound engineering principles.

6. A Title V Permit application shall be submitted to the District no later than 12 months after ATC Permit Issuance.