



## MOJAVE DESERT AIR QUALITY MANAGEMENT DISTRICT

14306 Park Avenue Victorville, CA 92392-2310  
760.245.1661 -- 800.635.4617 -- FAX 760.245.2022

**INACTIVE**

S002161

Inactive type Permit has no description information.

**EXPIRES LAST DAY OF: APRIL 2014**

### **OWNER OF OPERATOR (Co.#332)**

Caliber Collision  
2941 Lake Vista Drive  
Lewisville, TX 75067

### **EQUIPMENT LOCATION (Fac.#1550)**

Caliber Collision Center - I Ave  
11182 I Avenue  
Hesperia, CA 92345

#### **Description:**

SPRAY BOOTH, AUTOMOTIVE consisting of: Gen-Aire model No. 6AD-24-14-8, which consists of a fan rated at 3 hp and pulling 10,300 cfm through 15 fiberglass filters at 20"x20"x3".

#### **CONDITIONS:**

1. Operation of this equipment shall be conducted in compliance with data and specifications submitted with the application under which this permit is issued unless otherwise noted below. [Rule 204]

2. Total Spray Booth VOC emissions shall be less than 25 lbs/day. [Rules 1303; 204]

3. A daily log shall be maintained of the VOC's used and/or emitted from this facility. The log shall contain at least the following:

- A. Equipment by permitted number, or name of operation for unpermitted equipment, that uses material that contain VOC.
- B. Type of material, its use, and its applicable VOC limit in pounds per gallon (or grams per liter), by District Rule or Rules.
- C. Manufacturer of material, manufacturer product name, and/or code number.
- D. Quantity of each coating, solvent used, and its VOC content. (Note: Units must be consistent). If quantity used is in gallons (or liters), the VOC must be in pounds per gallon (or grams per liter). Units used in item B and D must be the same.
- E. Quality of acetone usage in gallons (or liters) per day.
- F. Copies of the Environmental Data Sheet and/or Material Safety Data Sheet (MSDS) for each coating, diluents, thinner, and solvent used.
- G. Differential pressure across outlet filters.

Fee Schedule: 7 (h)

Rating: 1 device

SIC: 7532

SCC: 40200110

Location/UTM(Km): 473E/3810N

This permit does not authorize the emission of air contaminants in excess of those allowed by law, including Division 26 of the Health and Safety Code of the State of California and the Rules and Regulations of the District. This permit cannot be construed as permission to violate existing laws, ordinances, statutes or regulations of this or other governmental agencies. This permit must be renewed by the expiration date above. If billing for renewal fee required by Rule 301(c) is not received by expiration date above, please contact the District.

Caliber Collision  
2941 Lake Vista Drive  
  
Lewisville, TX 75067

By: **COPY**  
**Brad Poiriez**  
Air Pollution Control Officer

[Rule 204]

4.The VOC log shall be kept current, on-site for a minimum of two years, retained for 2 years, and provided to District personnel on request. (NOTE: The daily log information provides a basis for the Toxic Emission Inventory required by AB 2588 and Title III requirements) [Rule 204]

5.This facility shall not emit more than 9.9 tpy of a single HAP and 24.9 tpy of all HAP's. To ensure compliance, the owner/operator shall calculate and record the annual emissions of Federal Hazardous Air Pollutants (HAP's) in tons per year (tpy) on a calendar year basis (January 1 through December 31). In lieu of calculating the annual emissions, this facility may record all solvent and coatings and the amounts used and have MSDS available and on site for all coatings and solvents used. The list of HAP's can be found in Section 112(b)(1) of the Federal Clean Air Act or at web site: <http://www.epa.gov/ttn/atw/188polls.html>. This calculation and/or required equivalent documentation shall be kept current, on-site for a minimum of two years, retained for 5 years, and be provided to District personnel on request. This calculation shall be expanded to cover all toxic substances, used at this facility, which are included in Appendix A of The Emission Inventory Criteria And Guidelines Report Criteria for the Air Toxics Hot Spots Program, adopted per the Air Toxics Hot Spots Information and Assessment Act (AB 2588, 1987, Connolly. The web site for Appendix A is: <http://www.arb.ca.gov/ab2588/final96/guide96a.pdf> [Rule 204]

6.A gauge shall be maintained to indicate, in inches of water, the static pressure differential across the exhaust filters. When in operation, the pressure differential shall not exceed 0.25 inch of water. [Rule 204]

7.This equipment shall be operated in compliance with Rules 442 and 1116 in their entirety. These rules pertain to volatile organic compound (VOC) containing solvents and Mobile Equipment Coating Operations respectively. [Rules 442; 1116; 204]

8.The owner/operator (o/o) shall not use any motor vehicle or mobile equipment coating that contains hexavalent chromium or cadmium (Section 17 CCR 93112 - Airborne Toxic Control Measure for Emissions of Hexavalent Chromium and Cadmium from Motor Vehicle and Mobile Equipment Coatings). Compliance with this condition shall be verified by retention of MSDS sheets (or equivalent documentation of chemical content) for applicable coating used at the facility for two (2) years, and provision of said information to District, State, or federal personnel upon request. [17 CCR 93112; Rule 204]

9.Pursuant to 40 CFR 63, subpart HHHHHH, this facility shall not spray apply coatings to metal and plastic surfaces that contain compounds of chromium (Cr), lead (Pb), manganese (Mn), nickel (Ni), or cadmium (Cd) .(Contact the MDAQMD for conditions if this facility will use the above mentioned toxic metals for additional permit requirements.) [40 CFR 63 subpart, HHHHHH; Rule 204]

10.Pursuant to 40 CFR 63 subpart HHHHHH, this facility shall not conduct any paint stripping operations on any substrate that use methylene chloride (MeCl)-containing paint stripping formulations after January 9, 2011. (Contact the MDAQMD for conditions is this facility will use and MeCl for additional permits requirements.) [40 CFR 63 subpart HHHHHH]