



MOJAVE DESERT AIR QUALITY MANAGEMENT DISTRICT

14306 Park Avenue Victorville, CA92392-2310
760.245.1661 -- 800.635.4617 -- FAX760.245.2022

INACTIVE

T009517

Inactive type Permit has no description information.

EXPIRES LAST DAY OF:AUGUST 2006

OWNER OF OPERATOR (Co.#9)

Searles Valley Minerals Operations, Inc
13200 Main Street
Trona,CA93562

EQUIPMENT LOCATION (Fac.#7)

SVM - West End Plant
80201 Trona Road
Trona,CA93562

Description:

TANK, BRINE consisting of:Hydrocarbon emissions, mainly kerosene outgassing from the brine is vented to a vapor recovery system and burned within the two Argus Boilers (B0000554, and B000555).

EQUIPMENT

Capacity	Equipment Description
10	Effluent Brine Tank (10,000 gallons)

CONDITIONS:

- 1.This equipment shall be operated and maintained in strict accord with the recommendations of its manufacturer or supplier and/or sound engineering principles.
- 2.The owner/operator, o/o, shall install, operate and maintain this tank and ancillary piping, valving, electrical and instrumentation consistent with those requirements to be compliant with District Rules 462 and 463.
- 3.This equipment shall be operated in compliance with all data and specifications submitted with the application under which this permit is issued unless otherwise noted below.

Fee Schedule:5 (a) Rating:10000gallons SIC:1474 SCC:40188898 Location/UTM(Km):464E/3951N

This permit does not authorize the emission of air contaminants in excess of those allowed by law, including Division 26 of the Health and Safety Code of the State of California and the Rules and Regulations of the District. This permit cannot be construed as permission to violate existing laws, ordinances, statutes or regulations of this or other governmental agencies. This permit must be renewed by the expiration date above. If billing for renewal fee required by Rule 301(c) is not received by expiration date above, please contact the District.

Searles Valley Minerals Operations, Inc
P.O. Box 367
Trona,CA93592-0367

By: **COPY**
Brad Poiriez
Air Pollution Control Officer

4.All gauge hatches, roof supports, manholes, automatic bleeder vents, rim vents, gauge wells, etc., shall be equipped with vapor-tight seals or breather vents set at no less than 10% of the maximum allowable working pressure of the roof.

5.This tank shall only be used for the storage of effluent Brine liquid.